			4				3	7	7		2		1		1				
I			ON THIS DRA		PROERTY OF C REPRODUCED, I				CELESTRA	WI	RE SIZE	BOLT	B	C	D	G	H]	
			FOR WHICH						CAT.NO DB021401F-261	CODE #2 AWG	FLEX 150/24 #2 Weld	SIZE 1/4	MIN 1.64	±0.04 0.68	±0.015 0.10	±0.02 1.00	±0.01 0.41		
D																		D	
NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.																			
			LIST	ED BY "UNE	DERWRITERS	SERIES OF CA INC." AND "C 24 STRANDED	SA" FOR USE		BOLT SIZE										
			OTH			AS NOT PEEP HE SUFFIX OF													
	M	IATERIAL:	HIGH	H CONDUCT		GHT COPPER			_ G										
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.												С					
									mire inspection hole										
		NSTALLATIO	ON GUIDE																
	D	IE CODE = IE COLOR =	33															\searrow	
								Beveled wire entry											
В					\checkmark											I		В	
Б			C	Jus	RoHS	1													
				ED															
			ZMVV/2/7/8	E513913															
																		_	
										ΗUY	R C	ELES							
A											76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.					n.			
									TITLE WIRE CONNECTORS AND SOLDERI									A	
									LUGS FOR CODE AND FLEX CABLE										
		-	Ruby Feng		Ce		ds Spec. Initialed.			RIAL HIGH-CONDU WROUGHT C	OPPER DB021	401F-26	1	CALE N	TS THE				
	REV	DATE	DWN	СНК		DESCRI		/		ELECTRO TIN	PLATE DWG. NO.	186-cp36	00 U	nit IN		Ψt]	
			4				3	L	\sum	2					1				