	-				ı									
		4		3	\downarrow	2					1			
ı			IE PROERTY OF CELESTRA, I	S	CELEST	RA W	IRE SIZE	BOLT	В	С	D	G	Н	1 '
		IFIDENCE AND NOT TO B FOR WHICH FURNISHED	E REPRODUCED, USED OR .		CAT.N	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01	1
			•		DB023801	F-261 #2 AWG	150/24 #2 Weld	?3/8	1.83	0.68	0.10	1.00	0.41]
_														
D	NOTE:	4 ALL DIMENCIO	NIC ADE IN INICHECTINI	ECC OTHEDWICE										D
	NOTE:	SPECIFIED.	ONS ARE IN INCHES UNL	ESS OTHERWISE	SE									
		2 ALL DA DRIA	,LB,WP AND J SERIES O	E CAT NO S ADE										
			NDERWRITERS INC." AN			BOLT SIZE								
]	ON CODE WIF	RES AND FLEX/24 STRAN											
		PRE-FIX CAT.	NO.WITH "L" HAS NOT PI		- C									
		OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.												
		WITH "P".			G									
	MATERIAL:	HIGH CONDU	CTIVITY WROUGHT COP	PER			, ,							
С	FINISH:		ELECTOR-TIN PLATE UNLESS OTHERWISE										l c	
			ATE PER MIL - T -16366. IO.WITH "SP" FOR SILVE		Color coded barrel markings									
										Ū				
					ر <u>ئ</u> ابئ	Cold!	√ Wire ir	spectio	n hole)				
				45,	\$ B □									
	INSTALLATION GUIDE DIE CODE = 33													\leftarrow
	DIE CODE = 33 DIE COLOR = Brown													
	Beveled wire entry													
							,				Ч			
_			. /											
В		c(Ui)us	V											В
			2002/95/EC											
		LISTED												
		WIRE CONNECTORS ZMVV/2/7/8.E513913												
								ELES	TRA	CO	RP∩!	2ΔΤΙ)N	1
						HU		76. Hua					_	
						www.huya		Panyu [
Α														A
, ,					WIKE CONNECTORS AND 30						DERING			
					LUGS	FOR CODI	E ANI) FL	EX C	CABLI	E			
	00 23-Aug-25	Ruby Feng Sinia Qiu	Celestra Sta	ndards Spec. Initialed.		MATERIAL HIGH-CONE WROUGHT	DUCTIVITY PRT. NO.	801F-261	S	CALE	TS THR	ID ANGLE PF	ROJECTION	1
	REV DATE	DWN CHK	+	CRIPTION	ECN	FINISH	DWG NO	186-cp36		INIIT	ICH 4	⊕ €	\Box	
	THE DATE		I I			ELECTRO TI	N PLATE	100-cp36	υ <u>ν</u>	IIV	ICH	+	7	1
	<u>-</u>	4		3	4	2					1			
					'									