		4			3				7 2				1												
I	DISCL	OSED IN CON	ON THIS DRA NFIDENCE AND FOR WHICH	D NOT TO BE	PROERTY REPRODU	OF CELESTRA, CED, USED OR	, IS			CELEST CAT.NO		WI CODE	RE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01						
	DISLO	SED EXCEPT	FOR WHICH	FORNISHED.						LB02140	1F	#2 AWG	60 Navy #4 We 125/24 = 50.5 kcmil		1.88	0.67	0.09	1.00	0.36						
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.															D									
			LIST	ED BY "UNI	DERWRIT	ID J SERIES C TERS INC." AN LEX/24 STRAI	ND "CSA	" FOR USE		BOLT SIZE															
			OTH			L" HAS NOT P IN THE SUFF																			
	М	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER G																							
С	FI	INISH:	SPE	CIFED PLA	TE PER N	ILESS OTHER AIL - T -16366. SP" FOR SILVE														С					
$\rightarrow$	D	INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown								Color coded barrel markings Wire inspection hole															
В	Beveled wire entry													В											
	-		2010 012770	2010810																					
												IUY vw.huyac		CELES 76. Hui Panyu	ancun	Rd. Zł	nongci	un Tow	-						
A											WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									A					
	00	23-Aug-25	Ruby Feng	Sinia Qiu		Celestra Sta	tandards	Spec. Initialed.			MATERI	AL HIGH-CONDU WROUGHT C	JCTIVITY PRT. NO.	021401F	S	ICALE N	TS THE		PROJECTION						
I.	REV	DATE	DWN	СНК		DES	SCRIPT	TION		ECN	FINISH	ELECTRO TIN	PLATE DWG. NO.	186-cp36	605 <sup>L</sup>	init in	ICH -	₩ E							
			4					3	4			2					1								