		4 3		\bigvee	√ 2		1															
1					PROERTY OF REPRODUCED	CELESTRA, IS			ELESTRA		RE SIZE	BOLT	В	С	D	G	Н	'				
			FOR WHICH		KLFKODOCLD	, OSLD OK			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01					
								LB0	23801F-250	#2 AWG	60 Navy #4 Weld 125/24 = 50.5	3/8	1.83	0.66	0.10	1.00	0.37					
											kcmil							l				
D																		D				
	N	IOTE:	1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.																			
							OF CAT.NO.S ARE															
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. BOLT SIZE																				
	1		PRE	DDE EIV CAT NO WITH "I " HAS NOT DEED HOLE LINI ESS																		
				IERWISE SP H "P".	ECIFIED IN	THE SUFFIX O	F THE CAT.NO.		- C C													
	М	IATERIAL:	HIG	H CONDUCT	TIVITY WRO	UGHT COPPER																
С													С									
						FOR SILVER.																
		Color coded barrel markings																				
\rightarrow	INSTALLATION GUIDE								Wire inspection hole									\leftarrow				
		DIE CODE = 33 DIE COLOR = Brown									Ì											
		Beveled wire entry																				
В	·											В										
			LOTED US	2002/95/EC																		
		WIR	LISTED RE CONNECTORS IVV/2/7/8.E513B13																			
											/ AR C	ELES	TRA	CO	RPOF	RATIO	NC					
										HUYA		CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town.										
										www.huyaco.com P		Panyu Dist. Guangzhou 511495.					١.					
Α								WIRE CONNECTORS AND SOL						_DER	RING A							
			LUGS FOR CODE AND FLEX CABLE							E												
	00	14-Dec-25	4-Dec-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.						MATE	RIAL HIGH-CONDU WROUGHT C	OPPER LB023	801F-250	S	CALE N	TS THR	Φ -	NGLE PROJECTION					
ı	REV	DATE	DWN	CHK		DESCRI	PTION	E	ECN FINISH	ELECTRO TIN	PLATE DWG. NO.	186-cp36 ⁻	16	nit In	CH	⊕ Ł	\perp					
			4				3	4		2					1							
								1														