		4			3	\bigvee	2					1			.
•			AWING IS THE PROE ID NOT TO BE REPRO	ERTY OF CELESTRA, IS ODUCED, USED OR		CELESTRA CAT.NO	WIRE		BOLT SIZE	A	B MIN	C	R	ID 10.01	
		CEPT FOR WHICH				CAT.NO	CODE	FLEX 125 Navy 1/0	SIZE	±0.06	IVIIIN	±0.04		±0.01	ł
						LA2038-250	2/0 AWG	Weld 275/24 =	3/8	2.63	0.84	0.85	1.79	0.45	
						LA2036-230	2/0 AVVG	111 kcmil	3/0	2.03	0.04	0.65	1.79	0.43	
D								133/.0282							D
	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE														
		SPI	ECIFIED.		Color coded marking										
					IES OF CAT.NO.S ARE										
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.					Bolt Size								
											l —				
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.														
	WITH "P"														
	MATER	AL: HIG	H CONDUCTIVIT	Y WROUGHT COPF											
	FINISH:					4				•					
С	FINISH:		ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.					В							С
		SUI	FIX CAT.NO.WIT	H "SP" FOR SILVER	₹.				•						
							•	4	-						
	INSTALI	ATION GUIDE													1
	DIE COI	E = 45													
	DIE COI	OR = Black			1	R	Inspecti	on Hol	е						
						J -						1			
						_ 🕇 🖺		/				A	$\vec{\mathcal{J}}$		
В						₽. †		i f			,	/	/		В
				2 V		<u> </u>					(
	Revoled entry														
		LISTED WIRE CONNECTOR					Bevele	dentry							
		WINE CONNECTION													
	ı									.== -					-
						HUY	7 A ® C	ELES					_		
											76. Huancun Rd. Zhongcun Town.				
۸							Panyu Dist. Guangzhou 511495.						,		
Α						WIRE CONNECTORS AND SO LUGS FOR CODE AND FLEX					D SOLDERING				A
			 								EX C	ABL	ABLE		
	00 00 5	25 Duku 5-	Cinic Oix	Calaatii Ci		MATERIAL HIGH-CONDU	CTIVITY PRT. NO.			CALE	THR	RID ANGLE PI	ROJECTION	-	
		2-25 Ruby Feng			ndards Spec. Initialed.	FON	WROUGHT CO	PPER LA20	38-250		NIT		Ф Е	\neg	
ı	REV DA		CHK	DESC	CRIPTION	ECN	ELECTRO TIN F	PLATE DWG. NO.	186-cp03	63	IN	СН	\P\ \]
		4			3	\triangle	2					1			
						I									