			4				3	\square	7		2				1			_	
I	THE IN		I ON THIS DRA NFIDENCE AND	WING IS THE	PROERTY O	F CELESTRA, IS			CELESTRA		RE SIZE	BOLT	В	С	D	G	Н]	
			FOR WHICH		INEL NODUCE	D, 00LD OK		F	CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01	4	
											75 Navy #2 Weld 150/24 = 60.5								
								ſ	DB011243F-2	50 #1 AWG	kcmil 175/24 =	1/2	3.01	0.75	0.09	1.75	0.42		
D											70.6 kcmil 133/.0223							D	
D	N	IOTE:	1. ALL	DIMENSION	NS ARE IN I	NCHES UNLES	S OTHERWISE	L			100,10220							1	
			SPE	CIFIED.															
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE																	
						RS INC." AND " X/24 STRANDE													
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.																		
									Ā										
	м	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																	
-		INISH:				ESS OTHERWIS						~		2					
С		INISH.			-	- T -16366.					0	3						С	
			SUF	FIX CAT.NC	D.WITH "SP	" FOR SILVER.													
									→ → Color coded barrel markings										
\rightarrow	IN	NSTALLATIO	ON GUIDE						p									4	
		IE CODE =							ŝ	- And	Wire ii	nspectio	on hole	•				\neg	
									45.	(die)	В			D		\vdash			
											K			L.					
						,			<u> </u>]	4					
В									Beveled wire entry								В		
					ROF 2002/95/	IS NEO													
			LIST	TED															
			WIRE CONN ZMVV/2/7/8																
												ELES		CO		ΖΔΤΙά	2N	1	
									+	HUY	\sim							1	
										www.huyac			76. Huancun Rd. Zhongc Panyu Dist. Guangzhou 5					1	
А																		A	
									WIRE CONNECTORS AND SOLDERING									1	
									LUGS FOR CODE AND FLEX CABLE							E			
	00	23-Aug-25	Ruby Feng	Sinia Qiu		Celestra Standa	ards Spec. Initialed.		M	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PRO WROUGHT COPPER DB011243F-250 NTS					ROJECTION	NC			
	REV	DATE	DWN	СНК		DESCR	IPTION		ECN FI	NISH ELECTRO TIN	DIMO NO	186-cp36		NIIT	CH -	ŒE			
			4		·		3	\wedge	· · ·	2	1	•			1			-4	
					I			4	_				I						