					_														
			4				3	∇			2				1			_	
1	THE IN		I ON THIS DRA NFIDENCE AND	WING IS THE		CELESTRA, IS		CELES			RE SIZE	BOLT	В	С	D	G	Н]	
			FOR WHICH		REPRODUCE	D, USED OR		CAT.	NO	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01		
							-				75 Navy #2 Weld 150/24 = 60.5								
								DB01124	3F-260	#1 AWG	kcmil 175/24 =	1/2	2.83	0.81	0.12	1.75	0.41		
											70.6 kcmil 133/.0223								
D	NI	OTE:	1 1			NCHES UNLESS					133/.0223							D	
		OTL.		CIFIED.			OTTERWISE												
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE																	
			LIST	ED BY "UN	DERWRITE	RS INC." AND "C													
	ON CODE WIRES AND FLEX/24 STRANDED CABLES.																		
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS																		
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".								BOLT SIZE										
			WIII	н "Р".															
		ATERIAL:				OUGHT COPPER						$\neg \varphi$	- <u> </u>	7					
С	FI	INISH:			PLATE UNLE TE PER MIL	ESS OTHERWIS	E					.						С	
						FOR SILVER.					~	3							
											Calaraa			Linner					
\sim	IN	INSTALLATION GUIDE							Color coded barrel markings										
		IE CODE =						بِي الله الله الله الله الله الله الله الل											
	D	IE COLOR =	= Green					5.2.	1	die tou	2	ispeciic		_	\square	\vdash			
								v			B	I	-	D Г					
														ŧ		<u> </u>			
в																		В	
D	B CULUS ROHS																		
					2002/95/	1 9									I				
			LIS WIRE CONN																
			ZM///2/7/8	E513913															
												CELES	STRA	CO	RPOF	RATIO	NC	1	
										IU	A	76. Hua	ancun	Rd. Zh	nongcu	in Tow			
									- w	ww.huyac	o.com	Dist. G	ist. Guangzhou 511495.						
А									TITLE WIRE CONNECTORS AND SOLDERING									A	
									LUGS FOR CODE AND FLEX CABLE										
																		_	
			Ruby Feng				rds Spec. Initialed.		MATERIAL HIGH-CONDUCTIVITY PRT. NO. WROUGHT COPPER DB011243F-260						CALE THRID ANGLE PROJECTION				
1	REV	DATE	DWN	СНК		DESCRI		ECN	FINISH	ELECTRO TIN	PLATE DWG. NO.	186-cp36	63	NIT IN	СН 4	ŒE			
			4				3	Δ		2					1				
					-			I											