			Д		I		3		7		2		1		1				
			ON THIS DRA		PROERTY OF CE REPRODUCED, U			\	CELESTRA	WI	RE SIZE	BOLT	B	C	D	G	Н	Ĭ	
			FOR WHICH						CAT.NO DB015601F-251	CODE #1 AWG	FLEX 225/24 #1 Weld	SIZE 5/16	MIN 1.76	±0.04 0.76	±0.015 0.12	±0.02 1.00	±0.01 0.46		
D														D					
	N	IOTE:		DIMENSION CIFIED.	IS ARE IN INCH	IES UNLESS	OTHERWISE												
	 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. 								BOLT SIZE										
			OTH		D.WITH "L" HAS PECIFIED IN TH														
	M	IATERIAL:	HIGI	H CONDUCT		HT COPPER						-							
С	F	INISH:	ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С					
									me inspection hole										
\sim	INSTALLATION GUIDE																		
	D	VIE CODE = 3	37																
									Beveled wire entry										
В			ر¶) c	L)us	RoHS													В	
			LIST	ED	ENGENERAL														
			WIRE CONN ZMVV/2/7/8	E513913															
A										IU	R C	ELES							
									ww.huyac			Huancun Rd. Zhongcun T 14 nyu Dist. Guangzhou 5114							
									TITLE	WIRE CONNECTORS A				ND SOLDERING				A	
										LUGS FOR CODE AND FLEX CABLE									
			Ruby Feng		Cel		ds Spec. Initialed.			RIAL HIGH-CONDI WROUGHT C	OPPER DB015	601F-25	1	CALE N	TS THE		ROJECTION		
	REV	DATE	DWN	СНК	1	DESCRI		/		ELECTRO TIN	DWG. NO.	186-cp36	71	nit IN	ICH -	Ψt		l	
			4				3	L		2					1				