						I									
		4			3	\downarrow		2				1			
ı			ING IS THE PROEF NOT TO BE REPRO	RTY OF CELESTRA, IS		CELEST		IRE SIZE	BOLT	В	С	D	G	Н	
	DISCOSED IN CO			DOCED, OSED OR		CAT.NO		FLEX		MIN		±0.015		±0.01	ł
						DB013801I	-261 #1 AWG	225/24 #1 Weld	?3/8	1.83	0.75	0.12	1.00	0.45	
D															D
	NOTE:	1. ALL DI SPECI		E IN INCHES UNLESS	S OTHERWISE										
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE BOLT SIZE														
			D BY "UNDERW ODE WIRES AND												
	1			H "L" HAS NOT PEEP				Huya	-(-X)-	<u></u>					
				ED IN THE SUFFIX O				7 7 1			<u>.</u>				
		WITH '	"P".					G							
	MATERIAL:	HIGH (CONDUCTIVITY	WROUGHT COPPER	₹			lo							
С	FINISH:	_	-	UNLESS OTHERWIS	E										С
				R MIL - T -16366. I "SP" FOR SILVER.		Color coded barrel markings									
						45°+3°	is Edd		spectior	n hole		_			
\rightarrow	INSTALLAT	ION GUIDE				4		B		7	D				4
	DIE CODE :										‡	1	\rightarrow		
	DIE COLOR	. = Green					Bev	eled wire entry	ı		1				
							Dev	eled wife entry				Ļ			
_				./											_
В		ւ(ՈՐ)IIS E	POHS											В
				002/95/EC											
		LISTE WIRE CONNECT													
		ZMVV/2/7/8.E51	13913												
		1 1						. 1							
							HU		ELES						
							www.huya		76. Huar Panyu D					٦.	
А							-								۸
A		TITLE WIRE CONNECTORS AND SOLD								Α					
							LUGS FOR CODE AND FLEX CABLE								
	00 23-Aug-25	Ruby Feng	y Feng Sinia Qiu Celestra Standards Spec. Initialed.				MATERIAL HIGH-CONI WROUGHT	DUCTIVITY PRT. NO. COPPER DB013	801F-261	S	CALE N		D ANGLE PRO	DJECTION	
	REV DATE	DWN	CHK	DESCR	IPTION	ECN	FINISH ELECTRO TI	5,116,116	86-cp367	8 0	NIIT	CH ($\bigoplus $ \in	\perp	
		4	1	1	3	\triangle	2		•	T		1			1
				I		T				I					