	•			_			T											
	4		3		\bigvee		2					1						
'				PROERTY OF CELES				CELESTRA		RE SIZE	BOLT	В	С	D	G	Н	<u>'</u>	
		EPT FOR WHICH		KEFKODOCED, OSEL	JOK		<u> </u>	CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01		
D						-	W	VP011458F- 193	#1 AWG	75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223	?1/4	1.23	0.68	0.11	0.62	0.41	D	
	NOTE:		DIMENSION CIFIED.	IS ARE IN INCHES	SUNLESS	OTHERWISE												
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.															_		
	WITH "P"											BOLT	SIZE					
	MATERIA	L: HIG	H CONDUC	FIVITY WROUGHT	COPPER	!			<u> </u>	Huya	-(1)-	- c						
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.												С					
	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green							Color coded barrel markings Wire inspection hole B D									\leftarrow	
В	CUL US LISTED WIRE CONNECTORS							Beveled wire entry										
_		ZM/V/227:															_	
									HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.									
Α								WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									А	
	00 24-Aug	00 24-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.							MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTION WROUGHT COPPER WP011458F-193 NTS									
	REV DAT		CHK		DESCRI			ECN FINIS		DIMO NO	458F-193 86-cp368	+	VIIT		\bigcirc \in	\exists		
		4				3	4		2		•			1	·			
	_						I											