		4		I	3	\downarrow	2	2	1		1		-	
'	DISCLOSED IN (CONFIDENCE AN	D NOT TO BE REP	ERTY OF CELESTRA, IS RODUCED, USED OR		CELEST CAT.N		RE SIZE FLEX	BOLT SIZE I	B C	D 04 ±0.015	G +0.02	H ±0.01	ı
D	DISLOSED EXC	EPT FOR WHICH	FURNISHED.			LB01143	3322	75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223		1.40 0.6		0.75	0.41	D
	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE													
	LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTUS DIVISION IN THE SUFFIX OF THE CAT NO.											-		
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER													
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С		
\rightarrow	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green					\$\$.	Color coded barrel markings Wire inspection hole B Beveled wire entry							
В	CUL US ROHS LISTED WIRE CONNECTORS ZMY/Y/Z/TA ESTABIS													
	ı		1				I							
						HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.								
А						WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								
	00 27-Oct-2		g Sinia Qiu Celestra Standards Spec. Initialed				MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER LB011434F			SCALE THRID ANGLE PROJECTION UNIT				
	REV DATE	4	CHK	DESC	3	ECN	electro tin	PLATE	186-cp3682		INCH 1	\$ -		