	_							1														
		4 3				$\forall$	7	2			1											
ı						OF CELESTRA, IS			CELESTRA	WI	RE SIZE	BOLT	В	С	D	G	Н	] '				
		LOSED IN CON DSED EXCEPT		D NOT TO BE I FURNISHED.	REPRODUC	ED, USED OR			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01	1				
С									LB011434FF 250	P- #1 AWG	75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223	1/4	1.38	0.70	0.11	0.75	0.42	D				
	N	IOTE:		DIMENSION CIFIED.	IS ARE IN	INCHES UNLESS	S OTHERWISE															
		2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																				
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".									BOLT SIZE												
	_	MATERIAL:																				
C		FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С									
+		INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green							Color coded barrel markings  Wire inspection hole  B D									$\leftarrow$				
В		CUL US ROHS LISTED WIRE CONNECTORS								Beveled wire entry												
_		ZMn	E-CONNECTORS VV/27/8 E513813															_				
									HUYA® Www.huyaco.com  CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.													
Д										WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE												
	00	14-Dec-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.							N	MATERIAL HIGH-CONDU WROUGHT C	JCTIVITY PRT. NO. OPPER LB0114	34FP-250	) S	CALE N	TS THR	ID ANGLE PR	GLE PROJECTION					
1	REV		DWN	СНК		DESCR			ECN F	INISH ELECTRO TIN	DIMO NO	186-cp369		NIIT	CH	<b>\Phi</b> E	$\exists$	] ,				
	_		4				3	$\uparrow$	Δ	2					1							