		4 3					7	2			11					.		
•			ON THIS DRA			OF CELESTRA, IS			CELESTRA	•	RE SIZE	BOLT	В	С	D	G	Н	· '
			FOR WHICH		NEI NODOC	EB, OOEB OK			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01	
D							-		LB013801FI 250	P- #1 AWG	75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223	3/8	1.83	0.70	0.11	1.00	0.42	D
	N(OTE:		DIMENSION CIFIED.	IS ARE IN	INCHES UNLESS	OTHERWISE											
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.													_			
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".											BOLT SIZE						
	М	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER									-\D							
С	FI	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.												С				
-	D	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green							Color coded barrel markings Wire inspection hole									\leftarrow
В	CULUS ROHS								<u> </u>	Beve	eled wire entry							В
_		2M ²	VV/2778 E513913															_
									HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.									
Α										WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								
	00	00 27-Oct-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.							N	MATERIAL HIGH-COND I	JCTIVITY PRT. NO.		S	CALE	THR	RID ANGLE PI	ROJECTION	
	REV		DWN	CHK		DESCRI			ECN F	WROUGHT O	DWG NO	01FP-250 86-cp369		NT IN	ICH -	+ E		
		· · · _	4				3	Δ	\	2	ITENTE	. 55 Spoot		111	1	Т	-	
					ı			7	_				ı					