_	_							ı																
		4 3				4	7	2			1													
ı						OF CELESTRA, IS			CELESTRA	WI	RE SIZE	BOLT	В	С	D	G	Н	] '						
		CLOSED IN CON LOSED EXCEPT			REPRODUC	ED, USED OR			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01	1						
									LB011434F-26	60 #1 AWG	75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223	?1/4	1.39	0.75	0.10	0.75	0.41	D						
		NOTE:		DIMENSION CIFIED.	NS ARE IN	INCHES UNLES	S OTHERWISE					'		•	•									
_	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																							
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																							
		MATERIAL:	HIGH	H CONDUC	TIVITY WR	OUGHT COPPE																		
C		FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE  SPECIFED PLATE PER MIL - T -16366.  SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С											
	>	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green							Color coded barrel markings  Wire inspection hole  B D									$\leftarrow$						
E	3	CUL US ROHS							Beveled wire entry															
_	_		ZMVV/2/7/8	E513913														_						
									HUYA® Www.huyaco.com  CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.															
P								TIT	WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE															
	00	23-Aug-25	Ruby Feng	Sinia Qiu		Celestra Standa	ards Spec. Initialed.		MA	ATERIAL HIGH-CONDU WROUGHT C		434F-260	S	cale N	TS THR	_	ANGLE PROJECTION							
1	RE	V DATE	DWN	СНК		DESCR	IPTION		ECN FIN	IISH ELECTRO TIN	DIMO NO	86-cp370		NIIT	iCH -	<b>(</b> E	$\exists$							
	_		4				3	4		2					1									