							-										
		4			3		\downarrow	$\sqrt{}$		2				1			
I				PROERTY OF CELESTI REPRODUCED, USED (LESTRA	L	RE SIZE	BOLT	В	С	D	G	Н	1 '
	DISCLOSED IN CO			REPRODUCED, USED C				15601FP-	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01	
							LB0	251	#1 AWG	225/24 #1 Weld	5/16	1.76	0.76	0.12	1.00	0.46	
											•		•		•		
D																	D
	NOTE:		DIMENSION CIFIED.	IS ARE IN INCHES U	JNLESS OTI	HERWISE											
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON COPE WIDES AND FLEX OF PANDED CAPLES. BOLT SIZE															
	ON CODE WIRES AND FLEX/24 STRANDED CABLES.														 		
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																
	MATERIAL:	HIGH	I CONDUCT	IVITY WROUGHT C	OPPER		G										
С	FINISH:	ELEC	CTOR-TIN P	LATE UNLESS OTH	IERWISE												С
C				E PER MIL - T -163 WITH "SP" FOR SIL													
		0011	17 071.110	.with or Tolkon				^	*/	Color co	ded bar	rel ma	rkings				
								. /		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \							
_	INSTALLATION GUIDE							Wire inspection hole									1
	DIE CODE =	37						4		B		-	Ľ		}		
	DIE COLOR	= Green						<u> </u>					 				
									Beve	led wire entry	•						
				,						,							
В		, (Ui)	_ V													В
				ROHS 2002/95/EC													
		LIST	ED														
		WIRE CONNE ZMVV/2/7/8.E															
	1																 —
									HUY		ELES						
											76. Hua					n.	
٨								-	www.huyac		Panyu [_
Α						WIRE CONNECTORS AND SOLDERING A									A		
		LUGS FOR CODE AND FLEX					EX C	CABL	İ								
	00 23-Aug-25	Ruby Feng	Sinia Qiu	Celestra	Standards S	Spec. Initialed.		MAT	ERIAL HIGH-CONDL WROUGHT C	JCTIVITY PRT. NO. LB015	601FP-25	s 1 S	CALE N	TS THE	RID ANGLE PE	ROJECTION	
1	REV DATE	DWN	СНК	D	ESCRIPTION	ON	E	CN FINIS	SH ELECTRO TIN	PLATE DWG. NO.	186-cp37	10	NIT IN	ICH -	(E	\exists	
	·	4			3		\triangle	•	2	•		j		1			'
	•			•								'					