	•															
		4			3		\downarrow	2						1		
ı				PROERTY OF CELESTE REPRODUCED, USED (CELEST		WIRE SIZE	BOLT	В	С	D	G	Н	'
		EPT FOR WHICH		REPRODUCED, USED C			LB015601		FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01	
							261	FP- #1 AW(225/24 #1 W	eld 5/16	1.70	0.75	0.12	1.00	0.45	
								•	•		•		•		•	
D																D
	NOTE:		DIMENSION CIFIED.	IS ARE IN INCHES U	JNLESS OTHI	ERWISE										
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE BOLT SIZE															
_		ON	CODE WIRE	S AND FLEX/24 STF	RANDED CAB	BLES.				_	\rightarrow	T DOLI	OIZL			_
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".															
	MATERIA	_: HIG	H CONDUC	TIVITY WROUGHT C	OPPER					G						
С	FINISH:	ELE	CTOR-TIN F	PLATE UNLESS OTH	IERWISE				1-	-1						С
C				ΓE PER MIL - T -1630 D.WITH "SP" FOR SIL												
		001						× */\	_Color	coded bar	rel ma	rkings				
							o ,		NA E.	_ :4:.						
_	INSTALLATION GUIDE							Wire inspection hole B D								
	DIE CODE	= 37					4				-	Ĺ		}		
	DIE COLO	R = Green										 				
								Be	eveled wire ent	· ·						
				,						,						
В		, (u	.)													В
				ROHS 2002/95/EC												
		LIS	TED													
		WIRE CON ZMVV/2/7/														
								шп	YA ®	CELES	STRA	CO	RPOI	RATIO	NC	
										76. Hu						
^								www.huy		Panyu						_
Α								TITLE WIR	E CONNE	CTORS	AND) SO	LDEF	RING		Α
						_		LUC	S FOR CC	DE AN	D FL	EX C	CABL	Е		
	00 23-Aug-	25 Ruby Feng	Sinia Qiu	Celestra	Standards Sp	ec. Initialed.		MATERIAL HIGH-CO WROUG	NDUCTIVITY PRT. NO)15601FP-26	S1 S	CALE N	TS	RID ANGLE PI	ROJECTION	
ı	REV DATE	DWN	CHK	D	ESCRIPTIO	N	ECN	FINISH ELECTRO	TIN PLATE DWG. N). 186-cp37	'17	TINIT IN	ICH -	(<u></u>	1
		4			3		\triangle	2	•		i		1			
	•			•			I				'					