							_											
		4				3		/		2				1			-	
	DISCLOSED IN COM	VFIDENCE AND	NOT TO BE F	PROERTY OF CELES REPRODUCED, USED				CELESTRA CAT.NO	WI CODE	RE SIZE FLEX	BOLT SIZE	B MIN	C +0.04	D ±0.015	G +0.02	H ±0.01		
	DISLOSED EXCEPT	F FOR WHICH F	URNISHED.					DB105601F-261	1/0 AWG	275/24 1/0 Weld	5/16	1.70	0.83	0.12	1.00	0.50		
							L										1	
D	NOTE:	1 ΔΙΙΓ		S ARE IN INCHES		THERWISE											D	
	NOTE.		CIFIED.		THERWISE													
			, , ,	B,WP AND J SERIE					~BOLT SIZE									
	LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS																	
_																		
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.									V								
	WITH "P".							G										
	MATERIAL:	HIGH	CONDUCT	IVITY WROUGHT	COPPER					2	4							
С	FINISH:	-	-	LATE UNLESS OT E PER MIL - T -16	-												С	
				WITH "SP" FOR S		Color coded barrel markings												
								45°+3°	die cold	Wire in	spectio	on hole	_	$ \longrightarrow $				
\rightarrow	> INSTALLATION GUIDE																	
	DIE CODE = DIE COLOR :														\geq		\neg	
									Beveled wire entry									
										·····,				L				
				~														
В		c(VL	.) _{US}	RoHS,													В	
				2002/95/EC														
		LIS I WIRE CONNE ZMVV/2/7/8.E																
_																	—	
-															ΟΛΤΙΛ	אר		
-								┼──┤┣	ΗUY				Rd. Zh					
-									ww.huyac				Guangz					
A								TITLE WIRE CONNECTORS AND SOLDER							ING		A	
-								LUGS FOR CODE AND FLEX CABLE										
\vdash			0	<u> </u>				MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTION									-	
	00 23-Aug-25 REV DATE	Ruby Feng	Sinia Qiu CHK		DESCRIPT	Spec. Initialed.		ECN FINIS		COPPER DB105	601F-26	_	N ⁻ INIT		€	\neg		
	ALV DATE	4		L		3	1	ECIN	ELECTRO TIN	I PLATE	86-cp37	41	IN	<u>сн '</u> 1	Ψ		J	
		4				2	4	7	Z					I				