								1										
		4 3		3	√ 2			1										
'					PROERTY OF OR			CELES		WIRE SIZE	BOLT	В	С	D	G	Н	1 '	
			FOR WHICH		KLFKODOCED,	OSED OR		CAT.N	O CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01		
								LB105601	F-250 1/0 AWG		5/16	1.76	0.76	0.12	1.00	0.46		
										kcmil 133/.0 254							ł	
D																	D	
	N	NOTE:		DIMENSION CIFIED.	IS ARE IN IN	CHES UNLESS	OTHERWISE											
						SERIES OF CA	AT NO S ABE											
			LIST	ED BY "UND	DERWRITERS	S INC." AND "C	SA" FOR USE											
	4		ON (CODE WIRE	S AND FLEX	/24 STRANDE	D CABLES.						BOLT	SIZE			1—	
							HOLE UNLESS			9		7	Ī					
		OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																
	N	MATERIAL:	HIGI	H CONDUCT	TIVITY WROL	JGHT COPPER	2			V			<u>†</u>					
С	l _F	FINISH:	ELE	CTOR-TIN P	LATE UNLES	SS OTHERWIS	E			G	i						С	
C			SPE	CIFED PLAT	TE PER MIL -	T -16366.												
	SUFFIX CAT.NO.WITH "SP" FOR SILVER. —Color coded barrel markings																	
									\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Color cod	ied barr	ei mai	rkings					
_	l .,	NOTALL ATIO					က္	Wire inspection hole										
		NSTALLATION DIE CODE =	42					45,	Jan .	В	•		D					
		DIE COLOR :	= Pink									~	F					
								<u> </u>					†					
						,			└Be	veled wire entry								
В			ران ال)													В	
					ROHS 2002/95/EC													
			LIST WIRE CON	ΓED		•												
			ZMVV/2/7/8															
	4																l—	
		1	1						<u> </u>									
									шп		ELES							
											76. Hua Panyu F					n.		
Α														Panyu Dist. Guangzhou 511495.				
		TITLE WIRE CONNECTORS AND SOLE																
									LUGS FOR CODE AND FLEX						CABLE			
	00	23-Aug-25	Ruby Feng	Sinia Qiu	С	elestra Standa	rds Spec. Initialed.		MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THR WROUGHT COPPER LB105601F-250 NTS						RID ANGLE PI	ROJECTION		
	REV	DATE	DWN	CHK		DESCRI	PTION	ECN	FINISH	5,110,110	186-cp375		NIIT	CH -	(E	\exists	.	
			4				3	Δ	2	•		i		1			'	
					ı							'						