	4					3	7	7		2					1				
I			DRAWING IS THI					CELESTR			RE SIZE	BOLT	В	C	D	G	Н]	
			HICH FURNISHED.		, OSED ON			CAT.NO		CODE	FLEX 100 Navy #1 We	SIZE	MIN	±0.04	±0.015	±0.02	±0.01	4	
								LB105601F-	-260 1/0	0 AWG	225/24 = 90.8		1.70	0.75	0.12	1.00	0.45		
											kcmil 133/.0 25	4						1	
D																		D	
	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.																		
	 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. 													DOLT	0175				
													—						
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																		
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																		
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.													С					
											Color c	oded bar	rel mai	rkings					
\rightarrow		INSTALLATION GUIDE DIE CODE = 42								Wire inspection hole									
F		ODE = 42 OLOR = Pink						4	/		B			D					
										+ -				$\frac{1}{2}$	$\left \right\rangle$	5			
		Beveled wire entry																	
В			\frown	~	/					Devel	eu wire entry					Ļ		В	
В		С	(VL) _{US}	RoHS	S,													В	
		_		2002/95/EC	7														
			LISIEU RE CONNECTORS																
	1																		
												CELES			יסס			1	
										UΥ		76. Hua							
										.huyaco		Panyu l							
А												TORS	ORS AND SOLDERING					A	
								LUGS FOR CODE AND FLEX CA											
								_									0.00000		
								MATERIAL HIGH-CONDUCTIVITY PRT. NO. WROUGHT COPPER LB105601F-260 NTS											
I.	REV D	ATE DV	/N CHK		DESCRI			ECN	FINISH EL	ECTRO TIN F	PLATE DWG. NO.	186-cp37	72	INIT	СН	Ψt			
		4				3	4	\square		2					1				
							I	I											