			4		1		2	\forall			2		ı		1			
	THEIN	JEODMATION	4	WINC IS THE	DDOEDTY (OF CELESTRA, IS	3	V	/		2 IRE SIZE	- o	<u> </u>		<u> </u>			,
	DISCL	OSED IN CON	NFIDENCE AND	NOT TO BE	REPRODUC	ED, USED OR			CELESTRA CAT.NO		FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	±0.02	H ±0.01	
D	DISLO	SED EXCEPT	FOR WHICH I	FURNISHED.					DB305601	3322	150 Navy 2/0 Weld 325/24 = 131 kcmi 133/.0316 259/.0227 427/.0177	ı	1.75	0.94	0.14	1.00	0.57	D
J	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.										-							
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.														_		
			OTH				P HOLE UNLESS OF THE CAT.NO.		BOLT SIZE									
	М	IATERIAL:	HIGH	H CONDUC	ΓΙVITY WR	OUGHT COPPE												
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.										G		'	Ý.				С
	D	INSTALLATION GUIDE DIE CODE = 50 DIE COLOR = Orange							Color coded barrel markings Wire inspection hole									\leftarrow
В		CUL US LISTED WIRE CONNECTORS ROHS 2002/95/EC							Beveled wire entry									В
			ZMVV/2/7/8															_
									HUYA® Www.huyaco.com CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.									
Α									WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									А
	00	23-Aug-25	Ruby Feng	Sinia Qiu		Celestra Standa	ards Spec. Initialed	d		MATERIAL HIGH-COND WROUGHT (UCTIVITY PRT. NO. COPPER DB3	DB305601F NTS					OJECTION	
I	REV	DATE	DWN	CHK		DESCR	IPTION		ECN	FINISH ELECTRO TIN	N PLATE DWG. NO.	186-cp38	49 ^U	nit IN	CH	⊕ €		
	_ 		4				3			2					1			