			4		I		3	4	7		2		1		1			
			ON THIS DRA		PROERTY OF CE REPRODUCED, U			N	CELESTRA	W	RE SIZE	BOLT	B	С	D	G	Н	
			FOR WHICH		KEFRODOCED, O	SED OK			CAT.NO DB303801F-261	CODE 3/0 AWG	FLEX 450/24 3/0 Weld	SIZE 3/8	MIN 1.83	±0.04	±0.015 0.14	±0.02	±0.01 0.63	
								ľ		I			I		1	1		
D																		D
	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.																	
			LIST	ED BY "UNE	B,WP AND J SE DERWRITERS I S AND FLEX/24	NC." AND "C	SA" FOR USE		BOLT SIZE									
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																	
	м	IATERIAL:	HIGI	H CONDUCT	TIVITY WROUG	HT COPPER					G							
С	FI	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.									rkings				С			
									ŝ	No.	Wire in	spectio	on hole	•				
	INSTALLATION GUIDE								Wire inspection hole									
	D	IE CODE =	50															
			Ū					Beveled wire entry										
																+		
В			<b>ر)</b> ا	L)US	,RoHS,													В
			LIST	FED	2002/95/EC													
			WIRE CON ZMVV/2/7/8															
												ELES	TRA		RPO	RATIO	ON	
												76. Hua	ancun	Rd. Zł	nongci	un Tow		
А										,		anyu Dist. Guang						A
									WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									
	00	01-Jul-25	Ruby Feng	Sinia Qiu	Cel	estra Standar	ds Spec. Initialed.		MATE	ERIAL HIGH-COND WROUGHT (	ICTIVITY PRT. NO.	- 7 (1 (1) 301F-26 <sup>2</sup>	S	CALE N	THE	RID ANGLE PF	ROJECTION	
1	REV	DATE	DWN	СНК		DESCRIF	•		ECN FINIS		DWO NO	86-cp38	_	NIT	ICH -	ŒE	$\square$	
			4	· · · · · · ·			3	4		2					1			·
								I										