

THE INFORMATION ON THIS DRAWING IS THE PROPERTY OF CELESTRA, IS DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR DISCLOSED EXCEPT FOR WHICH FURNISHED.

CELESTRA CAT.NO	WIRE SIZE		BOLT SIZE	B MIN	C ± 0.04	D ± 0.015	G ± 0.02	H ± 0.01
	CODE	FLEX						
DB401434F-260	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/0154	?1/4	1.39	1.02	0.14	0.75	0.63

D NOTE:




1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.
2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.

PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".

MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER

FINISH: ELECTRO-TIN PLATE UNLESS OTHERWISE SPECIFIED PLATE PER MIL - T -16366.
SUFFIX CAT.NO.WITH "SP" FOR SILVER.

INSTALLATION GUIDE
DIE CODE = 54
DIE COLOR = Purple



00	13-Feb-26	Ruby Feng	Sinia Qiu	Celestra Standards Spec. Initiated.	ECN
REV	DATE	DWN	CHK	DESCRIPTION	ECN

HUYA
www.huyaco.com

CELESTRA CORPORATION
76. Huancun Rd. Zhongcun Town.
Panyu Dist. Guangzhou 511495.

TITLE: WIRE CONNECTORS AND SOLDERING
LUGS FOR CODE AND FLEX CABLE

MATERIAL: HIGH-CONDUCTIVITY
WROUGHT COPPER

PRT. NO.: DB401434F-260

SCALE: NTS

THIRD ANGLE PROJECTION

FINISH: ELECTRO TIN PLATE

DWG. NO.: 186-cp3896

UNIT: INCH

