	-								I									
		4			3 🔻		$\sqrt{}$	2			1							
'		VFORMATION OSED IN CON				CELESTRA, IS D. USED OR			CELESTF CAT.NO	" .	WIRE SIZE	BOLT SIZE	B MIN	C .0.04	D	G ±0.02	H	'
		SED EXCEPT							LB253801	ED 0022	FLEX 250 kcmil 637	/24					±0.01	
									263	?	Class I, K, I		1.83	1.28	0.18	1.00	0.79	
D	,	IOTE:	4 011	DIMENSION			e OTHEDWICE											D
		IOTE:		CIFIED.	IS ARE IN II	NCHES UNLES	S OTHERWISE											
			2. ALL	DA,DB,LA,L	B,WP,AL,AS	S AND J SERIE	S OF CAT.NO.S	ARE										
						RS INC." AND " X/24 STRANDE	CSA" FOR USE						/	BOLT	SIZE			
	1										4	<u>a</u>		Ĭ.				—
							P HOLE UNLESS OF THE CAT.NO			—(<u>)</u>	·	Huya	- C	;				
			WIT	H "P".						2				V				
	N	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																
С	F	INISH:				SS OTHERWIS	SE											С
				CIFED PLAT FIX CAT.NC		FOR SILVER.					0.1							
										\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Color	coded bar	rel ma	rkıngs				
									_{წ2} /		-Wir	e inspectio	on hole	9				
_	, IN	NSTALLATIO	N GUIDE						45° ±3°	piece	В	•		D				4
		DIE CODE = 0 DIE COLOR =												_				7
									<u>v</u>					1				
	Beveled wire entry																	
В																_		В
Ь		- 1		V														Ь
		C (RoHS 2002/95/EC	1													
			ISTED E CONNECTORS (V/2/7/8 E513813		•													
	1																	
												CELES	STR4	CO	RPO	RATIO	ON	
							<u> </u>			HU	Y A [®]	76. Hu						
	-									www.huyaco.com Panyu Dist. Guangzhou					zhou 5	11495.		
Α										TITLE WIRE CONNECTORS AND SOLDERING A								
									+-	LUGS FOR CODE AND FLEX CABLE								
		0 16-Dec-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.							MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PRO.							ROJECTION		
	00 REV		DWN	CHK			IPTION		ECN	FINISH	DWG NO	53801FP-26		INIIT	TS	6	\Rightarrow	
	IVE V	DAIL	4	CHIN	ı	DLJCK	3			ELECTRO 2	TIN PLATE	186-cp39	104 I	IN.	ICН 1	¥ ,		l
	-		4		I		3	Z	7	۷					ı			