| _ | | | | | 1 | | | | | | | | | |
|---------------|--|---|--|---------------------|-----------------|---------------|---|-----------------|----------|----------|--------------------|--------------|----------------|------------|
| | | 4 | | 3 | \bigvee | | 2 | | | | | 1 | | |
| ı | | | E PROERTY OF CELESTRA, E REPRODUCED, USED OR | S | | LESTRA | | SIZE | BOLT | В | С | D | G H | |
| | | FOR WHICH FURNISHED | | | | AT.NO | CODE | FLEX | | MIN | | ±0.015 ± | | _ |
| | | | | | LB ² | 111434F | 400 kcmil | 400 Navy | 1/4 | 1.93 | 1.41 | 0.17 | 0.75 0.8 | ' - |
| | | | | | | | | | | | | | | |
| D | | | | | | | | | | | | | | D |
| | NOTE: | ALL DIMENSIC SPECIFIED. | NS ARE IN INCHES UNL | ESS OTHERWISE | | | | | | | | | | |
| | 2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE BOLT SIZE | | | | | | | | | | | | | |
| | | | BOLI SIZE | | | | | | | | | | | |
| | - | | ES AND FLEX/24 STRAN | | | | | Huya | _(| | | | | |
| | | | NO.WITH "L" HAS NOT P SPECIFIED IN THE SUFF | | | | | \mathcal{I} | X | | V | | | |
| | OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". | | | | | | | | , | | | | | |
| | MATERIAL: | HIGH CONDUC | CTIVITY WROUGHT COF | VITY WROUGHT COPPER | | | | | | | | | | |
| С | FINISH: | | ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. | | | | | | | | | | | С |
| | | | Color coded barrel markings | | | | | | | | | | | |
| | | | | | | | | / | | | | | | |
| | | | | | | 45° ±3 | Pis Ford | Wire in | spection | | _ | \leftarrow | | |
| \rightarrow | INSTALLATION GUIDE | | | | | $\frac{B}{B}$ | | | | | | | | 4 |
| | DIE CODE = | | | | | <u> </u> | 1 | | | <u> </u> | \ | | | 7 |
| | DIE GOLOIK | - Bido | | | | | Bevele | ed wire entry | ' | | 1 | | | |
| | | | | | | | Dovoic | od wile chary | | | | | | |
| _ | | | | | | | | | | | | | | |
| В | 1 . | | • | | | | | | | | | | | В |
| | c (| UL) US ROH! | § | | | | | | | | | | | |
| | | ISTED RE CONNECTORS | • | | | | | | | | | | | |
| | ZA | RE CONNECTORS VV/2/7/8.E513813 | | | | | | | | | | | | |
| | - | | | | | | | | | | | | | |
| | | | I | | | | | . 1 | | | | | | 4 |
| | | | | | | | HUY | lack R lack C | | | | | ATION | |
| | | | | | | | www.huyaco | | | | | ongcun | | |
| А | | | | | | | www.huyaco.com Panyu Dist. Guangzhou 51149 TITLE WIRE CONNECTORS AND SOLDERING | | | | | | | - A |
| ^ | | | | | | | VVIRE | | | | | | | ^ |
| | | | | | | | LUGS F | FOR CODE | AND |) FLI | EX C | ABLE | | |
| | 00 27-Oct-25 | Ruby Feng Sinia Qiu | a Qiu Celestra Standards Spec. Initialed. | | | MATE | ERIAL HIGH-CONDUC WROUGHT COR | | 1434F | S | cale NT | 'S _ | ANGLE PROJECTI | N |
| | REV DATE | DWN CHK | DES | CRIPTION | E | CN FINIS | ELECTRO TIN PI | _ATE DWG. NO. 1 | 86-cp406 | 0 0 | nit IN (| сн (€ | | |
| | | 4 | | 3 | Δ | | 2 | | | | | 1 | | _ |
| | | | • | | I | | | | | • | | | | |