					1										
		4		3		:	2		1		1				
ı			PROERTY OF CELESTRA, IS		CELESTR	A WI	RE SIZE	BOLT	' В	С	D	G	Н	ì '	
		FIDENCE AND NOT TO BE FOR WHICH FURNISHED.	REPRODUCED, USED OR		CAT.NC	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01		
					DB511243F	250 500 kcmil	500 Navy	1/2	3.01	1.54	0.22	1.75	0.95		
_														_	
D	NOTE:	4 ALL DIMENCION	IC ADE IN INICHES LINI E	CO OTHERWICE										D	
	NOTE:	SPECIFIED.	IS ARE IN INCHES UNLE												
		2 ALL DA DRIAL	DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE												
			DERWRITERS INC." AND		BOLT SIZE										
		ON CODE WIRE													
		PRE-FIX CAT.N	O.WITH "L" HAS NOT PEI												
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.														
		WITH "P".		G											
	MATERIAL:	HIGH CONDUC	TIVITY WROUGHT COPP	ER				7							
С	FINISH:		PLATE UNLESS OTHERW	/ISE										С	
•			TE PER MIL - T -16366. D.WITH "SP" FOR SILVER		Color coded barrel markings										
		OOT IX OAT INC		•			/ 2010. 222			9-					
					, , ,	The State of the S	✓ Wire in	spectio	n hole)					
									В						
\rightarrow		INSTALLATION GUIDE													
,	DIE CODE = 87 DIE COLOR = Brown														
	Beveled wire entry														
						2010	ned who endy					\sqcup			
			,												
В		ر (ار ال	_ V											В	
			ROHS 2002/95/EC												
		LISTED													
		WIRE CONNECTORS ZMVV/2/7/8.E513913													
	1													l —	
							- A - C		TDA				201	1	
						HUY					RPOF		_		
						www.huyac					nongcu zhou 51		11.		
Α														Α	
		TITLE WIRE CONNECTORS AND SO) SO	LDERING A							
		LUGS FOR CODE AND FLEX CAB						CABL	Ε						
	00 23-Aug-25	Ruby Feng Sinia Qiu	Colorino Cia-	dards Spec. Initialed.		MATERIAL HIGH-COND	UCTIVITY PRT. NO.		S	CALE		ID ANGLE PE	ROJECTION		
						WROUGHT (DWG NO	243F-250		INIIT	TS -	⊕ €	\neg		
	REV DATE	DWN CHK	DESC	RIPTION	ECN	ELECTRO TIN	I PLATE 1	86-cp40	84 "	IN	ICH	₩ L	7	J	
		4		3	4	2					1				
	•				I										