					1			_	L									
		4 THE INFORMATION ON THIS DRAWING IS THE PR					3		_	2		<u> </u>		1			-	
	DISCL	OSED IN CON	IFIDENCE AND	D NOT TO BE I	PROERTY OF C REPRODUCED,				CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	B MIN	C +0.04	D ±0.015	G +0.02	H ±0.01	
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.					DB511243F-26		500 Navy	1/2	2.83	1.52	0.23	1.75	0.95	1
															•			1
Р																		
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE													D				
				CIFIED.														
								-BOLT SIZE										
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS																	-
				IERWISE SP H "P".	PECIFIED IN T	HE SUFFIX O												
									G G									
		IATERIAL:																
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.																	С
			SUF	FIX CAT.NO).WITH "SP" F	OR SILVER.		Color coded barrel markings										
								شWire inspection hole										
•									45.23									
\rightarrow	INSTALLATION GUIDE DIE CODE = 87																	
	D	IE COLOR =	= Brown					<u> </u>										
									Beveled wire entry									
															I			
В															В			
					2002/95/EC	ľ												
				ED		•												
			ZMVV/2/7/8															
A																		-
										Ηυ		76. Hu						
													76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.					
									TITLE WIRE CONNECTORS AND SOLDERING								A	
									LUGS FOR CODE AND FLEX CABLE									
		MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE TH								THR		ROJECTION	-					
	00 Rev	23-Aug-25 DATE	Ruby Feng	Sinia Qiu CHK	C	DESCRI		d.		WROUGHT C	DWG N	511243F-26	0	INIT.	TS -	€	\neg	
	KEV	DATE		CHK		DESCRI	3	,		ELECTRO TIN	I PLATE	^{186-cp40}	185	IN	ICH 1	Ψ -		J
			4		I		3	Z	\vdash	Z					I			