		4		3	\bigvee	2			<u> </u>		1		1	,
	DISCLOSED IN CON	ON THIS DRAWING IS THE IFIDENCE AND NOT TO BE			CELESTRA CAT.NO	WIRE CODE	SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	R	ID ±0.01	
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNL			NLESS OTHERWISE	LA3038P-260	3/0 AWG	150 Navy 2/0 Weld 325/24 = 131 kcmil 133/.0316 259/.0227 427/.0177		2.65	0.83	0.90	1.82	0.50	D
_	SPECIFIED. 2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER											_		
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. B A									С				
→	INSTALLATION GUIDE DIE CODE = 50 DIE COLOR = Orange R Inspection Hole												\leftarrow	
В	B CONGCTOR NEBS3 ES CE											В		
						Beveled	a entry							
А							A 7		ncun F Dist. Gu	Rd. Zh uangz SOL	ongcu hou 5'	in Tow 11495. RING	'n.	A
						MATERIAL HIGH-CONDUC		- AINL		CALE		LID ANGLE P	ROJECTION	
	00 02-Dec-25 REV DATE	Ruby Feng Sinia Qiu DWN CHK		Standards Spec. Initialed. SCRIPTION	ECN	WROUGHT CO	DPPER LA303	8P-260		NT	S +	(h) -[7	
	NEV DATE	4		3	A	electro tin i	PLATE 1	86-cp041		IN	<u>сн </u> 1	Ψ -		