	-		4				3	$\downarrow$	7	:	2				1				
I	DISCL	OSED IN CON	IFIDENCE AND	) NOT TO BE F	PROERTY OF CEL REPRODUCED, US	ESTRA, IS ED OR			CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	]	
	DISLC	SED EXCEPT	FOR WHICH	FURNISHED.			]	-	LB513801FP 250		500 Navy	3/8	1.82	1.54	0.22	1.00	0.95	1	
D								-								•		D	
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.																		
			LIST	ED BY "UNE	B,WP AND J SE DERWRITERS II S AND FLEX/24	NC." AND "C		BOLT SIZE											
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																	
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER									(	G								
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Color coded barrel markings											С						
									Ì					•					
$\rightarrow$	INSTALLATION GUIDE DIE CODE = 87 DIE COLOR = Brown								Wire inspection hole										
	Beveled wire entry																		
В			ິ													<b></b>		в	
					2002/95/EC														
			WIRE CON ZMVV/2/7/8																
																		-	
										HU		ELES							
A										www.huyac					Rd. Zhongcun Town Jangzhou 511495.				
										ITTLE WIRE CONNECTORS AND SOLDERING A   LUGS FOR CODE AND FLEX CABLE A									
		00.405	Distriction		0.14				M		JCTIVITY PRT. NO.		S	CALE	THR		ROJECTION		
	00 Rev	DATE	Ruby Feng	Sinia Qiu CHK	Cele	DESCRI	ds Spec. Initialed. PTION				DWG, NO.	301FP-28	_	NIT	ICH	<b>(</b>	$\square$		
	<b>ـــــ</b>	1	4	<u> </u>			3	4	\	2		- <del>F</del> - 1			1			J 	
								I											