			4				3	4	7		2		I		1			
I	DISCL	OSED IN CON	ON THIS DRA IFIDENCE AND FOR WHICH) NOT TO BE F	PROERTY OF	CELESTRA, IS , USED OR			CELESTRA CAT.NO	A WI	RE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	1
	DISLO	SED EXCEPT	FOR WHICH	FORNISHED.					LB511243FF 260	500 kcmil	500 Navy	?1/2	2.83	1.55	0.23	1.75	0.95	
D																		D
	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.																	
			LIST	ED BY "UNE	DERWRITER	SERIES OF C S INC." AND " /24 STRANDE		BOLT SIZE										
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																	
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPERG																	
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.												С				
	Color coded barrel markings																	
\rightarrow	INSTALLATION GUIDE DIE CODE = 87 DIE COLOR = Brown								Wire inspection hole								\leftarrow	
												*						
_										Beve	eled wire entry							
В			c(V	L)US	RoHS	5												В
			280 072778															
A										HUY		76. Hu	6. Huancun		A CORPORAT			
													Panyu Dist. Guangzhou 511495.					A
										WIRE CONNECTORS AND SOLDERING								
	00	01-Jul-25	Ruby Feng	Sinia Qiu	C	celestra Standa	ards Spec. Initiale	ed.	N	ATERIAL HIGH-COND WROUGHT (UCTIVITY PRT. NO. COPPER LB511	243FP-26	50 S	CALE N	TS			
I	REV	DATE	DWN	СНК		DESCR	RIPTION		ECN F	ELECTRO TIN	I PLATE DWG. NO.	186-cp41	l 05	init IN	ICH -	0 E]
			4				3	4	7	2					1			