			4		I		3	7	7		2		I		1			
Ι					PROERTY OF CI				CELESTRA CAT.NO		IRE SIZE	BOLT SIZE	B MIN	C +0.04	D ±0.015	G ±0.02	H ±0.01	]
	DISLO	SED EXCEPT	FOR WHICH I	FURNISHED.					DB651243F-25		646 kcmil 1600/24		3.01	1.95	0.30	1.75	1.20	1
D																		D
	N	OTE:		DIMENSION CIFIED.	IS ARE IN INC	HES UNLESS	OTHERWISE											
_			LIST	ED BY "UNE	B,WP AND J S DERWRITERS S AND FLEX/2	INC." AND "C	SA" FOR USE		BOLT SIZE									
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																	
		IATERIAL:									-2							
С	FI	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.													С			
$\rightarrow$	INSTALLATION GUIDE DIE CODE = 94 DIE COLOR = Green								Wire inspection hole B B Beveled wire entry									
В		EXAMPLE 2002/95/FEC															В	
	-																	—
									HUYA			<b>ELESTRA CORPORATION</b> 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.						
A									TITLE WIRE CONNECTORS AND SOLDERING   LUGS FOR CODE AND FLEX CABLE									A
			Ruby Feng		Ce		ds Spec. Initialed.			ITERIAL HIGH-COND WROUGHT	COPPER DB651	243F-25	1	CALE N	TS THR			
	REV	DATE	DWN 4	СНК		DESCRI	3	Ĺ		electro tir	N PLATE	86-cp41	40	IN	існ   1	ΨĽ		]