_						I									
		4			3	\downarrow		2				1			
I		ON THIS DRAWING VEIDENCE AND NOT				CELEST		VIRE SIZE	BOLT	В	С	D		┌	
		T FOR WHICH FURNI		OCED, OSED OR		CAT.NO		FLEX	SIZE	MIN		±0.015		_	
						DB111241I	F-262 1000 kcmi	1000 Navy	1/2	2.33	2.17	0.33	1.25 1.3	54	
D														D	
	NOTE:			IN INCHES UNLESS	OTHERWISE										
		SPECIFIE													
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE BOLT SIZE														
			WIRES AND												
	1	PRE-FIX (CAT.NO.WITH	"L" HAS NOT PEEP	HOLE UNLESS		—(())) —	Huya	-(-/	- 	;				
		OTHERW	ISE SPECIFIE	D IN THE SUFFIX O							<u> </u>				
		WITH "P".						G	i						
	MATERIAL:	HIGH CO	NDUCTIVITY \	WROUGHT COPPER	₹			'							
С	FINISH:		ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.										С		
				'SP" FOR SILVER.		Color coded barrel markings									
	Wire inspection hole														
_	INSTALLATION GUIDE						BDD								
	DIE CODE = 125 DIE COLOR = White														
	DIE COLOR	= vvnite					\Boy	reled wire entry	ı		T				
							ъе	reled wife entry				Li			
				,								·			
В		_ (Uı),	IC D	V										В	
			JS K	075 02/95/EC											
		LISTED WIRE CONNECTORS													
		ZMVV/2/7/8.E513913													
	1													1_	
									ELES	TRA	COF	RPOR	ATION	1	
							HU						n Town.		
_							www.huya	co.com	Panyu [Dist. G	uangzl	hou 511	1495.	-	
Α								WIRE CONNECTORS AND SOLDERING							
						LUGS FOR CODE AND FLEX CABLE									
	00 23 Aug 35	Puby Fong Cini	Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.				MATERIAL HIGH-CON	DUCTIVITY PRT. NO.		S	CALE	THRID	ANGLE PROJEC	TION	
	00 23-Aug-25 REV DATE		a Qiu CHK	DESCRI		ECN	WROUGH	COPPER DB111	241F-262	_	NT NIT	$-$ 1 \ll		↓	
	NLV DATE		/1 IX	neocki			ELECTRO 1	IN PLATE	186-cp41	8/	INC	CH	Ŧ <u> </u>	<u>'</u>	
		4			3	4	2			1		1			