		4		3	4	7	2	2				1			
ı			THE PROERTY OF CELES		Ĭ	CELESTRA	WII	RE SIZE	BOLT	. В	С	D	G	Н	l '
		NFIDENCE AND NOT TO T FOR WHICH FURNISH) BE REPRODUCED, USED IED.	OR		CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01	
						LB113801F	1000 kcmil	1000 Navy	3/8	2.80	2.27	0.30	1.00	1.40	
_															l _
D															D
	NOTE:	ALL DIMEN SPECIFIED	SIONS ARE IN INCHES												
				-0.0F.0AT.NO.0.ADF											
			LA,LB,WP AND J SERIE "UNDERWRITERS INC.		BOLT SIZE										
			VIRES AND FLEX/24 ST												
	1	PRE-FIX CA	T NO WITH "I " HAS NO	:	- C - C										
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.														
		WITH "P".		G											
	MATERIAL:	HIGH CONE	UCTIVITY WROUGHT	COPPER	ي ح										
С	FINISH:	ELECTOR-1	IN PLATE UNLESS OT	HERWISE											С
C			PLATE PER MIL - T -16		✓ Color coded barrel markings										
		SUFFIX CA	Г.NO.WITH "SP" FOR S	ILVER.)	\ `	Color coo	eu ban	Ci illa	ikiliys				
						ů/		/ Wire in	snectio	n hole	2				
				45,	pie go,		эрссио	II HOIC		\leftarrow	\vdash				
\rightarrow	INSTALLATION GUIDE					$\frac{B}{A}$								4	
	DIE CODE =					•					‡				7
	DIL COLOR	= vviiite					Paye	lad wira antm	ı		1				
							ъече	led wire entry							
												ı	I		
В			V												В
		C(AF)	RoHS												
		LISTED	ZOUZISUEO												
		WIRE CONNECTORS ZMVV/2/7/8.E513913													
	1														 —
		<u> </u>	I			1 1									
							HUY					RPOF			
												nongci			
							www.huyac	o.com	anyu L	Jist. G	uangz	zhou 5´	11495.		
Α				TIT	TLE WIRE	CONNECT	ORS	AND	SO	LDER	RING		Α		
		LUGS FOR CODE AND FL													
	\vdash					3.41			_ / \ \ \ L		CALE		RID ANGLE PE	O IECTION	
	00 01-Jul-25	+		a Standards Spec. Initiale	ed.		ATERIAL HIGH-CONDU WROUGHT C	OPPER LB1	13801F		N	TS	_	OJECTION	
1	REV DATE	DWN CH	K	DESCRIPTION		ECN FIN	NISH ELECTRO TIN	PLATE DWG. NO.	86-cp41	88	init In	ICH H	(E		ı
		4		3	Δ		2					1			
			ı		Т					'					