			_		1			4	7				1								
		JEODI METON	4			051 5050 10	3		/	_	2				1						
	DISCL	OSED IN CON	VFIDENCE AND	NOT TO BE		CELESTRA, IS D, USED OR			CELESTRA CAT.NO	CODE	IRE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01				
	DISLO	SED EXCEPI	FOR WHICH	FURNISHED.					DB141058A-2	#1/-#10	-	#10	1.16	0.38	0.06	0.63	0.18				
								L		70		<u> </u>		<u> </u>	<u> </u>			l			
D																		D			
	N	OTE:		DIMENSION CIFIED.	NS ARE IN IN	NCHES UNLESS	OTHERWISE														
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE								B——B											
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																			
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS								J' J D												
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".								- 05° × 2°												
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																				
С	FI	INISH:			PLATE UNLE TE PER MIL	SS OTHERWIS	E		Beve	eled wire entr	y H							С			
						FOR SILVER.															
		INSTALLATION GUIDE DIE CODE = -								Wire inspection hole —BOLT SIZE											
\rightarrow																					
	D	IE COLOR :	=						-((-)—————————————————————————————————————	\$ C										
									A		1										
						,				<	G⊸∽				Die ¢	olor					
В	Color coded barrel markings								_		В										
			1103		2002/95/E																
			WIRE CONN ZMVV/2/7/8																		
	1																				
											/ AR C	ELES	TRA	CO	RPOI	RATIO	NC				
										HU		76. Hua					n.				
Α									www.huyaco.com Panyu Dist. Guangzhou 511495.								\dashv ,				
^										WIRE CONNECTORS AND SOLDERING A											
										LUGS FOR CODE AND FLEX CABLE											
	00								ATERIAL HIGH-COND WROUGHT	COPPER DB141	058A-25)		TS THE	RID ANGLE PI	ROJECTION	TION				
1	REV	DATE	DWN	CHK		DESCR		_	ECN FI	NISH ELECTRO TII	N PLATE DWG. NO.	186-cp41	97	nit IN	ICH -	⊕ Ł	\Box				
			4				3	4	\overline{A}	2					1						
								I													