									1										
			4				3		7		2				1			,	
•				WING IS THE NOT TO BE		CELESTRA, IS D, USED OR			CELESTR.	A CODE	/IRE SIZE	BOLT SIZE	B MIN	C +0.04	D +0.015	G ±0.02	H ±0.01	•	
	DISLOSE	D EXCEPT	FOR WHICH	FURNISHED.					LB141434A							1			
									260	AWG	_	1/4	1.39	0.41	0.05	0.75	0.17		
_																			
D	NOT	Γ ⊏ ·	1 ΔΙΙ	DIMENSION	IS ADE IN I	NCHES UNLES	S OTHERWISE											D	
		· L.		CIFIED.	NO AILL IIV I	INOTILO DINELO	5 OTTILITY/ISL												
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE								B → P										
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																	
	1																		
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.								9° ½5										
	WITH "P".											-							
	MAT	ΓERIAL:	HIGI	H CONDUC	TIVITY WRO	OUGHT COPPE	3												
С	FINI	ISH:		CTOR-TIN F		ESS OTHERWIS	E		Bev	eled wire ent	y	-						С	
						FOR SILVER.			*** 11 ***										
								Wire inspection hole											
\rightarrow		INSTALLATION GUIDE								BOLT SIZE									
		CODE = -																	
												_			Dia	`alar			
В									Die Çolor									В	
Ь		Color coded barrel markings									s— []]			Ь					
		WIRE	ISTED CONNECTORS V/2/7/8 E513913		•														
																		_	
												CELES	TRA	/ CO	RPO	RATIO	NC		
										HU	YA	76. Hua					_		
																Guangzhou 511495.			
Α										WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									
	00 28	00 28-Oct-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.							MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PRO.								ROJECTION		
		DATE	DWN	CHK		DESCR		····	ECN	WROUGHT FINISH ELECTRO T	DWG N			INIT	IS ICH	1	\exists		
	,	-	4		I	323311	3	/	1 2011	2	IN PLATE	100 0042		111	1	T			
			r		I		J	_	Τ'	_			I		'				