			4		I		3	7	7		2				1				
I					PROERTY OF (REPRODUCED,				CELESTRA CAT.NO		VIRE SIZE	BOLT SIZE	B MIN	C ±0.04	D +0.015	G ±0.02	H ±0.01		
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.					LB141434AF			1/4	1.39	0.41	0.05	0.75	0.17		
									200	ANG									
D	N	OTE:		DIMENSION CIFIED.	IS ARE IN IN	CHES UNLES	S OTHERWISE												
			LIST	ED BY "UNI	DERWRITER	SERIES OF C. S INC." AND "(/24 STRANDE													
			OTH			AS NOT PEEP THE SUFFIX C		D D									_		
	м	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																	
С	F	INISH:	NISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.							Beveled wire entry									
										/Wire inspection hole									
\rightarrow	► INSTALLATION GUIDE DIE CODE = -																		
		IE COLOR =																	
						,									Die ¢	olor			
В	B Color coded barrel markin								arkings	;	В								
					2002/90/20														
			ZM/V/2/7/8	E513913															
			1															<u> </u>	
										HU		ZELES							
A										www.huya					ancun Rd. Zhongcun Tc Dist. Guangzhou 51149				
									WIRE CONNECTORS AND SOLDERING									А	
									h			E AN		EX C		E RID ANGLE PF			
	00 Rev	23-Aug-25 DATE	Ruby Feng	Sinia Qiu CHK	С	celestra Standa	Irds Spec. Initialed	l.		WROUGH	COPPER LB141	434AP-20	50	N	TS .	Đ-E			
	, \ L V		4			DLOON	3			ELECTRO ⁻		100-0042		IN	існ 1	Ý	1		
L					I								1						