			4		I		3	7	7		2		1		1				
I					PROERTY OF CE				CELESTRA	W	RE SIZE	BOLT	В	С	D	G	Н		
			FIDENCE AND		REPRODUCED, U	ISED OR			CAT.NO	CODE	FLEX #8 Weld 37/24 =	SIZE	MIN				±0.01		
									DB081058A	#8 AWG	14.9 kcmil	#10	1.25	0.42	0.08	0.63	0.22		
_																		_	
D	N	IOTE:		DIMENSION	NS ARE IN INCH	HES UNLESS	OTHERWISE											D	
			2. ALL	DA,DB,LA,L	.B,WP AND J SI	ERIES OF CA				<	E	3	~						
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																	
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS									<sup>↑</sup> D				—					
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																		
	М	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																	
С	F	INISH:			PLATE UNLESS TE PER MIL - T				Beve	ed wire entry								С	
					D.WITH "SP" FC														
										∠—Wire i	nspection hole								
		INSTALLATION GUIDE DIE CODE = 21 DIE COLOR = Red								-BOLT SIZE									
	D																		
			- Neu						+		EQUAL C								
											-G>				Die Co	plor			
В				)	V									rlinge	/			В	
			C	<b>P</b> us	RoHS 2002/95/EC						Color co	ued bai	nei ma	arkings					
			ZM////2/7/8	E513913															
																		—	
										HU		ELES	STRA		RPO	RATIO	ON		
												76. Hua Panyu I					n.		
А										www.huyaco.com Panyu Dist. Guangzhou 511495.								А	
									WIRE CONNECTORS AND SOLDERING										
	00	22 440 25	Ruby Feng	Sinia Qiu		ostro Stondor	de Spee Initialed		MA	TERIAL HIGH-COND	JCTIVITY PRT. NO.			CALE	THR	ND ANGLE PF	ROJECTION		
	REV		DWN	CHK		DESCRI	ds Spec. Initialed. PTION		ECN FIN		DWG NO	81058A 186-cp42	208 U	INIT IN	ICH	Ð E	$\square$		
			4		<u>                                     </u>		3			2		. 50 op 42		IN	1	Ŧ			
					I								I						