	-		4		1		3	7	+		2		ı		1			
	THEI	NEORMATION	I ON THIS DRA	WING IS THE	PROFRTY O	CELESTRA, IS	<u> </u>		V CELESTRA		IRE SIZE	BOLT	<u> I</u> В	С	D I	G	Н	1
	DISCL	OSED IN CON	NFIDENCE ANI F FOR WHICH	NOT TO BE					CAT.NO	CODE	FLEX	SIZE	MIN	_		±0.02	±0.01	l
	DISEC	JSED EXCEPT	I FOR WHICH	FURINISHED.					DB083801A-25	50 #8 AWG	#8 Weld 37/24 = 14.9 kcmil	3/8	1.84	0.63	0.05	1.00	0.23	
									,	l	1				·	1		
D																		D
	١	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.																
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE								B								
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																
	1	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS																
		OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".								-9° **								
	N	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.						Beveled wire entry————————————————————————————————————											
						FOR SILVER.												
										\	:							
										Wire inspection hole —BOLT SIZE								
		NSTALLATIONE =															\leftarrow	
		DIE COLOR :	= Red						-(=									
_						,				→	-G>				Die ¢	olor		_
В	Color coded barrel markings								· '		В							
			1101	TEN .	2002/95/	ē												
			WIRE CONF															İ
									ши		ELES							
А									HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Tow Panyu Dist. Guangzhou 511495									
																		Α
										WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								
	<u> </u>								NA/	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTION								
		23-Aug-25					rds Spec. Initiale	ed.		WROUGHT	COPPER DB083	801A-250	<u> </u>	N.	TS .	T T		
1	REV	DATE	DWN	CHK	<u> </u>	DESCR				ELECTRO TII	N PLATE	86-cp42	13 "	IN	ICH 1	Ψ -		1
	-		4				3	Δ		2					1			