			4		1		2	_			0		ı		1						
	THE IN	NEORMATION	4 I ON THIS DRA	WING IS THE	PROFRTY OF	CELESTRA, IS	3	\	CELECTRA		2 IRE SIZE	DOLT.	<u> </u>	С	<u> </u>	G					
	DISCL	OSED IN CON	NFIDENCE ANI I FOR WHICH	NOT TO BE					CELESTRA CAT.NO	CODE	FLEX	BOLT SIZE	B MIN	_	D ±0.015	±0.02	H ±0.01				
	DISLO	JOED EXCEPT	T T OR WITHOUT	I OKINISITED.					DB081058A-260	#8 AWG	#8 Weld 37/24 = 14.9 kcmil	#10	1.15	0.41	0.08	0.62	0.23				
										1		1			ı	1					
D																		D			
	N	IOTE:		DIMENSION CIFIED.	NS ARE IN I	NCHES UNLESS	S OTHERWISE														
						J SERIES OF CA		B													
						RS INC." AND "C X/24 STRANDE															
	1	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS								ů ů D											
				IERWISE SF H "P".	PECIFIED IN	I THE SUFFIX O		-00													
	M	MATERIAL:	HIGI	H CONDUC	TIVITY WRO	OUGHT COPPER															
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.							Beveled wire entry————————————————————————————————————									С				
						FOR SILVER.															
										\/\/iro	inspection halo										
_	l	INSTALLATION GUIDE								Wire inspection hole  —BOLT SIZE											
	D	DIE CODE =	21														$\leftarrow$				
		DIE COLOR :	= Red						-		<u>₹</u> + ¢										
											_										
В					V	/				<b>⊸</b>	-G⊸⊳l				) Die C	OIO		В			
		CUL)US ROHS								Color coded barrel markings—											
			LIST	TED .																	
			WIRE CONF ZMVV/2/7/8																		
_	-																	—			
												ELES	TRA	CO	RP∩	RATI	NC				
										HŲΊ		76. Hua	ncun	Rd. Zł	nongci	un Tow					
									www.huyaco.com Panyu Dist. Guangzhou 511495.								┨,				
Α						_		TITL	WIRE CONNECTORS AND SOLDERING A												
										LUGS FOR CODE AND FLEX CABLE											
									ERIAL HIGH-COND WROUGHT	COPPER DB081	058A-260	)		TS THE	RID ANGLE PI	ROJECTION	TION				
1	REV	DATE	DWN	СНК		DESCR			ECN FINI	ELECTRO TIN	N PLATE DWG. NO.	86-cp42	14	NIT IN	ICH .	<b>Ψ</b> L					
			4				3	_		2					1						
					•				I				-					-			