| | | | 4 | | | | 3 | | \bigvee | | | 2 | | | | 1 | | | _ | |
|---|--|---|---|------------|-------------|------------------------------|---------|-----------|-----------|---|--|---------------|-------------------------------|-----------|------|-------------|-------------|------------|----------------|--|
| ' | | | ON THIS DRA | | | F CELESTRA, IS D, USED OR | | | | CELESTRA CAT.NO | | IRE SIZE | BOLT SIZE | B MIN | C C | D +0.015 | G ±0.02 | H ±0.01 | · | |
| | DISLO | SED EXCEPT | FOR WHICH | FURNISHED. | | , | | | Η. | | CODE | #8 Weld 37/24 | _ | | | | | | 1 | |
| | | | | | | | | | L | LB083801A | #8 AWG | 14.9 kcmil | 3/8 | 2.10 | 0.56 | 0.06 | 1.00 | 0.22 | 1 | |
| | | | | | | | | | | | | | | | | | | | _ | |
| D | | IOTE: | 1 11 | DIMENSION | IC ADE IN I | NCHES UNLESS | CTUEDWI | ICE | | | | | | | | | | | D | |
| | l in | IOTE. | | CIFIED. | NO ARE IN I | NOTES UNLESS | OTHERW | ISE | | | | | | | | | | | | |
| | | | | | | J SERIES OF C | | | ⊳——B——⇒ | | | | | | | | | | | |
| | | LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. | | | | | | | | | | | | | | | | | | |
| | 1 | PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. | | | | | | | | | | | | | | | | | — | |
| | | | | | | | | | | | | | | | | | | | | |
| | | WITH "P". | | | | | | | | | | | | | | | | | | |
| | N | MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER | | | | | | | | | | | | | | | | | | |
| С | F | FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE | | | | | | | | Beveled wire entry H | | | | | | | | | | |
| | SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. | | | | | | | | | → □ № | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | /—Wire inspection hole | | | | | | | | | |
| 4 | . 11 | INSTALLATION GUIDE | | | | | | | | BOLT SIZE | | | | | | | | | | |
| | | DIE CODE = 21 DIE COLOR = Red | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | Bio | Color | | | |
| В | | | | | | | | | | | ₩- | -G⊸⊳l | | | |) Bie Ç | .0101 | | l B | |
| Ь | | | | | | | | | | Color coded barrel markings | | | | | | | | | | |
| | | CUL US ROHS | | | | | | | | | | | | | | | | | | |
| | | WIR ZM | LISTED RE CONNECTORS VV/2/7/8.E513B13 | | • | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | |
| | 1 | | | | | | | | | | | | | | | | | | — | |
| | | | | | | | | | | | | 7 A @ | CFI FS | STRA | CO | RPO | RATIO | NC | | |
| | | | | | | | | | | HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. | | | | | | | | | | |
| | | | | | | | | | | | www.huyaco.com | | Panyu Dist. Guangzhou 511495. | | | | | | | |
| Α | | | | | | | | | | ТІТ | WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE | | | | | | | | | |
| | | | | | | | | | \dashv | | | | | | | | | | | |
| | | 00 28-Oct-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed. | | | | | | | \dashv | MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID AND | | | | | | | RID ANGLE P | ROJECTION | | |
| | REV | | DWN | CHK | | DESCR | | illiaitu. | \dashv | ECN FIN | WROUGHT (| DWG NO | 3083801A 186-cp42 | 22 | TIMI | TS . | 6 E | \Box | | |
| | \ \ \ \ | DAIL | 4 | OT IIX | <u> </u> | DEJUN | 3 | | Λ | LOIN | ELECTRO TIN | NPLATÉ | 100-CP42 | .33 | IN | ICН 1 | ¥ - | 7 | ¹ | |
| | - | | 4 | | 1 | | J | | 4 | | ۷ | | | I | | ' | | | | |