	,																
	4		3			7	7 2					1					
ı				PROERTY OF CELEST				CELESTRA		RE SIZE	BOLT	В	С	D	G	Н	
	DISCOSED IN COI			REPRODUCED, USED	OR			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01	
						•		LB083801A	#8 AWG	#8 Weld 37/24 = 14.9 kcmil	3/8	2.10	0.56	0.06	1.00	0.22	
								,		1 110 11011111							
D																	D
D	NOTE:		DIMENSION CIFIED.	IS ARE IN INCHES	UNLESS	OTHERWISE											D
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE									Ε	B						
	ON CODE WIRES AND FLEX/24 STRANDED CABLES.																
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".									D D							
	MATERIAL:	HIGH	I CONDLIC	TIVITY WROUGHT	COPPER												
				PLATE UNLESS OT				D									
С	FINISH:	SPEC	CIFED PLAT	TE PER MIL - T -163 D.WITH "SP" FOR S	366.	Ξ		Bevei	ed wire entry	/ H ←							С
		0011	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,														
						—Wire inspection hole											
_	INIOTALL ATION OF IDE							BOLT SIZE									1
		INSTALLATION GUIDE DIE CODE = 21															
	DIE COLOR :	= Red						<b>(</b> )		\$ C							
								A		±							
		_							<b>→</b>	-G>				Die Co	nolo		
В												В					
	COlor coded barrel markings										_						
		TZLL	FN	2002/30/20													
		WIRE CONNE ZMVV/2/7/8.E	ECTORS 513913														
	1																_
								Τ.		<b>7 A C C</b>	ELES	TDA		יסמם		ואכ	
								<del>                                     </del>	HUY		76. Hua						
									www.huyac	1	Panyu [						
Α										TITLE WIRE CONNECTORS AND SOLDERING							
								DDE AND FLEX CABLE						Α			
		LUGS FOR C												FOR COD			
	00 23-Aug-25	Ruby Feng	Sinia Qiu	Celestra	a Standar	ds Spec. Initialed		MA	ERIAL HIGH-CONDI WROUGHT C	COPPER LB0	83801A	S	cale N	TS THR	RID ANGLE PF	OJECTION	
	REV DATE	DWN	СНК		DESCRIF	PTION		ECN FINI	SH ELECTRO TIN	I PLATE DWG. NO.	186-cp42	33	nit In	CH -	(H)	$\dashv$	,
		4				3		7	2			i		1			'
				'								1					