			4		1		2		7		2		ı		1				
	THEIN	VEORMATION	4 I ON THIS DRA	WING IS THE	PROFRTY OF	CELESTRA, IS	3	\	CELECTRA		2 IRE SIZE	DOL T	<u> </u>	С	<u> </u>	G		i	
	DISCL	OSED IN CON	NFIDENCE AND FOR WHICH	NOT TO BE					CELESTRA CAT.NO	CODE	FLEX	BOLT SIZE	B MIN	_	D ±0.015		H ±0.01	1	
	DISLO	JOLD LACEF	T T OK WITHCIT	TORNISTIED.					LB081058A-250	#8 AWG	#8 Weld 37/24 = 14.9 kcmil	#10	1.16	0.41	0.08	0.63	0.23		
										-1									
D																		D	
	N	IOTE:		DIMENSION CIFIED.	NS ARE IN II	NCHES UNLESS													
		 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE 								B B									
						XS INC." AND "C X/24 STRANDEI													
	1	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS								, , , , , , , , , , , , , , , , , , ,									
				IERWISE SF H "P".	PECIFIED IN	THE SUFFIX O		-%											
	M	MATERIAL:	HIGI	H CONDUCT	TIVITY WRC	UGHT COPPER													
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.							Beveled wire entry									С		
						FOR SILVER.													
								∕—Wire inspection hole											
_	l .,									BOLT SIZE									
→	D	NSTALLATIONE CODE =	21														\leftarrow		
		IE COLOR :	= Red						-		<u>8</u> ← C								
В					V	/				⊸	-G⊸⇒l) Die C	olor		l B	
		c (UL) us RoHs								Color coded barrel markings—									
			LIST	TED															
			WIRE CONF ZMVV/2/7/8																
	ļ																	 —	
			Ι						T .		- A c O		TD ^	00	יסחסי	DATI	261		
									+	HUY		ELES 76. Hua							
									www.huyaco.com Panyu Dist. Guangzhou 511495										
Α										WIRE CONNECTORS AND SOLDERING A							Α		
								LUGS FOR CODE AND FLEX CABLE											
	00	23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					MA	ERIAL HIGH-COND WROUGHT	UCTIVITY PRT. NO. COPPER LB081)58A-250									
1	REV	DATE	DWN	СНК		DESCR	PTION		ECN FINI	SH ELECTRO TIN	N PLATE DWG. NO.	86-cp42	34 U	nit IN	ICH -	⊕ Ł	\Box		
			4				3			2					1				
								l	ı										