								l									
		4			3			2		1							
•				PROERTY OF CELES				CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D +0.015	G ±0.02	H ±0.01	
	DISLOSED	EXCEPT FOR WHI	CH FURNISHED.					LB083801AP)_	#8 Weld 37/24 =							
								250	#8 AWG	14.9 kcmil	3/8	1.84	0.60	0.05	1.00	0.23	
D																	D
D	NOTE		LL DIMENSIO PECIFIED.	NS ARE IN INCHE													
		L	ISTED BY "UN	LB,WP AND J SER IDERWRITERS INC ES AND FLEX/24 S	C." AND "CS		B V										
		C		IO.WITH "L" HAS N PECIFIED IN THE													
	MATE			TIVITY WROUGH	T COPPER	R											
С		FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.							Beveled wire entry————————————————————————————————————								
	/—Wire inspection hole																
\rightarrow		INSTALLATION GUIDE							BOLT SIZE								
	DIE CODE = 21 DIE COLOR = Red																
В			\odot	V					₩-	-G⊸⊲				Die Çi	olor		В
Ь	COlor coded barrel markings						/										
		L	STED	2002100120													
			CONNECTORS 1/2/7/8.E513913														
	1																
	1	<u> </u>		1						. 1							
									HUY		ELES					_	
									www.huyac		76. Hua Panyu I					11.	
А								TITLE WIRE CONNECTORS AND SOLDERING								Α	
		00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.						LUGS FOR CODE AND FLEX CABLE									
	00 23-							М	ATERIAL HIGH-CONDI WROUGHT (801AP-25		CALE N	TS THE	RID ANGLE PI	ROJECTION	
	$\overline{}$	ATE DWI	-		DESCRIP	TION		ECN FI	NISH ELECTRO TIN	DWG NO	186-cp42		NIT	ICH -	(E	\exists	
		4				3		Δ	2	I		i		1			
	•			•				l				•					