									1				•					
			4				3		\overline{V}		2				1			
•			ON THIS DRA NFIDENCE AN			CELESTRA, IS D, USED OR			CELESTRA CAT.NO	CODE	IRE SIZE FLEX	BOLT SIZE	B MIN	C +0.04	D +0.015	G ±0.02	H ±0.01	·
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.							#8 Weld 37/24 =				1			
									LB081458A-20	80 #8 AWG	14.9 kcmil	1/4	1.26	0.41	0.08	0.62	0.23	
_																		_
D	l N	IOTE:	1 ΔΙΙ	DIMENSION	IS ARE IN II	NCHES UNLESS	CTHEDWISE											D
	"	IOTE.		CIFIED.	NO ARE IN I	NOTILS UNLLS	OTTLKWISE											
		 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. 							P B									
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.									S D								
		WITH "P".																
	M	MATERIAL:	HIG	H CONDUC	TIVITY WRO	UGHT COPPER	1											
С	F	INISH:			PLATE UNLESS OTHERWISE TE PER MIL - T -16366.				Beve	Beveled wire entry H								С
						FOR SILVER.		- 11 12 12 12 13 14 14 15 15 15 15 15 15 15 15 15 15 15 15 15										
										Wire inspection hole								
\rightarrow		INSTALLATION GUIDE								BOLT SIZE								
	DIE CODE = 21 DIE COLOR = Red																	7
		()																
															Dia	color		
В		⊸-G-⊸										В						
Ь									Color coded barrel markings—								D	
		C US ROHS																
		WIF ZM	.ISTED RE CONNECTORS VV/2/7/8.E513913		,													
	1																	
												ELES	TRA	CO	RPO	RATIO	ON	
										76. Huancun Rd. Zhongcun Town.							_	
										www.huyaco.com Panyu Dist. Guangzhou 51						11495.		
Α									TI	TITLE WIRE CONNECTORS AND SOLDERING								Α
									LUGS FOR CODE AND FLEX CABLE									
	00	29-Oct-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					 d.	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PRO. WROUGHT COPPER LB081458A-260 NTS							ROJECTION			
	REV		DWN	CHK		DESCRI			ECN FI	WROUGHT	DWG NO	458A-260 186-cp424		NIIT	ICH	()	\exists	
			4		I		3	,	1 - 3 · · ·	2	TI EATE	20 op 12		111	1	1		
			•		ı		-	Z	Τ'	_			I					