			4				3	\downarrow	2	2				1				
I	DISCL	OSED IN COM		D NOT TO BE F	PROERTY OF CELE REPRODUCED, USE			CELESTRA CAT.NO	WIRE CODE	SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	R	ID ±0.01		
P]		DA4056-260	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	5/16	1.90	0.70	1.02	1.20	0.56		
D	N	OTE:		DIMENSION CIFIED.	S ARE IN INCHE		Color coded marking								D			
	 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. 							Bolt Size										
			PRE OTH	-FIX CAT.NC	S AND FLEX/24 : D.WITH "L" HAS I ECIFIED IN THE	NOT PEEP H	HOLE UNLESS	ļ										
	м	IATERIAL:	HIGI	HIGH CONDUCTIVITY WROUGHT COPPER					P									
С	F	INISH:	SPE	CIFED PLAT	LATE UNLESS C E PER MIL - T -1 WITH "SP" FOR	6366.		-		<u>В</u> А	-						С	
\rightarrow	D	ISTALLATIO IE CODE = IE COLOR =	54					1-	R	Inspect	ion Hol	е					\triangleleft	
В			D	i ^a N	EBS	B RoHS	CE		Bevele	d entry			E				В	
A									HUY www.huyaco	A	ELES 76. Hua Panyu I	ancun	Rd. Zh	iongcu	in Tow			
									TITLE WIRE CONNECTORS AND SOLDERING A LUGS FOR CODE AND FLEX CABLE A									
	00	23-Aug-25	Ruby Feng	Sinia Qiu	Celes	stra Standarc	ds Spec. Initialed.		MATERIAL HIGH-CONDU WROUGHT CO	OPPER DA4	056-260	60 SCALE THRID ANGLE PROJECTIO						
	REV	DATE	DWN	СНК		DESCRIP		ECN	FINISH ELECTRO TIN	PLATE	186-cp04	25 U	NIT IN	CH -	Ф-E		l	
	_ 4 3						3	4	2					I				