			4		1		3	_	17		2		ı		1			
	THEIN	VEORMATION	I ON THIS DRA	WING IS THE	PROFRTY OF	CELESTRA, IS	<u> </u>		V CELESTRA		IRE SIZE	BOLT	l B	С	D I	G	Н	ı
	DISCL	OSED IN CON	NFIDENCE AND FOR WHICH	NOT TO BE					CAT.NO	CODE	FLEX	SIZE	MIN	_		±0.02	±0.01	
	DISLO	JOED EXCEPT	I FOR WHICH	FURINISHED.			_		DB061058A-25	0 #6 AWG	#6 Weld 61/24 = 24.6 kcmil	#10	1.16	0.46	0.08	0.63	0.27	İ
										1	1			Į.	·Į	•		
D	_N	IOTE:	1 All	DIMENSION	NS ARE IN I	NCHES UNLESS	SOTHERWISE											D
	.,	.012.		CIFIED.	10 / 11 / 11	101120 0112200		_										
	 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE 								B → J									
						X/24 STRANDE												 —
			OTH				HOLE UNLESS F THE CAT.NO.		D D									
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																	
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.						Beveled wire entry									С		
						FOR SILVER.												
									—Wire inspection hole									
\rightarrow	IN	INSTALLATION GUIDE DIE CODE = 24 DIE COLOR = Blue								BOLT SIZE								
											1 1 1 1 1 1 1 1 1 1							
						,				V	-G				Die C	olor		
В										Color coded barrel markings								В
			LIST	[ED	2002/95/	ec.												
			WIRE CON ZMVV/2/7/8															
_																		
												ELES	TRA	CO	RPO	RATIO	NC	
									HUYA® 76. Huancun Rd. Zhongcun To www.huyaco.com Panyu Dist. Guangzhou 51149							un Tow		'
А										WWW.Hdyaco.com Panyd bist. Gdang2riod 311493.								Α
										LUGS FOR CODE AND FLEX CABLE								
	00	23-Aug-25	Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.						MA	MATERIAL HIGH-CONDUCTIVITY PRT. NO. WROUGHT COPPER DB061058A-250 NTS							ROJECTION	
	REV		DWN	СНК		DESCRI			ECN FIN	ISH ELECTRO TII	DWG NO	186-cp42		NIIT	ICH .	() [
			4				3			2			<u> </u>		1			'
									I									