			4				3	4	7	:	2				1				
I	DISCLO	OSED IN CON	VFIDENCE AND	NOT TO BE	PROERTY OF CELE REPRODUCED, USE				CELESTRA CAT.NO	CODE WI	RE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	I	
	DISLOS	SED EXCEPT	FOR WHICH	-URNISHED.					DB061034A-250		#6 Weld 61/24 = 24.6 kcmil	#10	1.28	0.46	0.08	0.75	0.27		
								1											
D	N	OTE:		DIMENSION CIFIED.	NS ARE IN INCHE	S UNLESS	OTHERWISE											D	
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.										3								
			OTH		O.WITH "L" HAS I PECIFIED IN THE		D D												
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																		
С	FI	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.								Beveled wire entry									
	/—Wire inspection hole																		
$\rightarrow$		INSTALLATION GUIDE DIE CODE = 24																$\leftarrow$	
		IE COLOR =									G				Die Ço	lor			
В	$\mathbf{A}$									Color coo	led bai	rel ma	ırkings				В		
			2011/07/20178	E513913															
			1		1				1 1										
												76. Hua	ancun	Rd. Zł	nongcu	RATIC In Tow 11495			
А														INS AND SOLDERING					
									+		FOR CODE								
			Ruby Feng		Celes		ds Spec. Initialed.			ERIAL HIGH-CONDU WROUGHT C	COPPER DB061	)34A-25	0	CALE N			OJECTION		
	REV	DATE	DWN	СНК		DESCRIP		Л		ELECTRO TIN	I PLATE	86-cp42	71	nit IN	СН   1	Ф-E			
			4				3	4	$\Delta$	2					I				