		4	1	2	+				ı		4			
			THE PROERTY OF CELESTI		CELESTRA	CELESTRA WIRE SIZE		BOLT	<u> I</u> А	В	С		ID	
		NFIDENCE AND NOT TO T FOR WHICH FURNISH) BE REPRODUCED, USED (ED.	DR	CAT.NO	CODE	FLEX	SIZE	±0.06	MIN	±0.04	R	±0.01	
					DA4014-251	4/0 AWG	550/24 = 222 kcmil 4/0 Weld	1/4	2.13	0.78	1.19	1.35	0.65	
D	NOTE:	SPECIFIED. 2. ALL DA,DB,I LISTED BY 'ON CODE W	GIONS ARE IN INCHES U LA,LB,WP,AL,AS AND J UNDERWRITERS INC." /IRES AND FLEX/24 STE T.NO.WITH "L" HAS NO	Color coded marking Bolt Size									D	
		OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".												
	MATERIAL:	HIGH COND	UCTIVITY WROUGHT C			В								
С	FINISH:	SPECIFED F	IN PLATE UNLESS OTH PLATE PER MIL - T -163 T.NO.WITH "SP" FOR SIL	A A									С	
-	INSTALLATION GUIDE DIE CODE = 54 DIE COLOR = Purple				R Inspection Hole									\leftarrow
В	NEBS3 E CE Beveled entry Beveled entry												В	
_	1													
						HUY www.huyaco	A	ELES 76. Hua Panyu [incun	Rd. Zh	nongci	ın Tow	_	
А				WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
	00 01-Dec-25	Ruby Feng Sinia (Qiu Celestra	Standards Spec. Initialed.		MATERIAL HIGH-CONDU WROUGHT CO	CTIVITY PRT. NO. DPPER DA40	14-251	S	cale N		IID ANGLE PE	ROJECTION	
1	REV DATE	DWN CH	K D	ESCRIPTION	ECN	FINISH ELECTRO TIN	PLATE DWG. NO. 1	86-cp04	30	nit IN	CH -	⊕ £	ightharpoons	
		4		3	\triangle	2					1			