													·					
		4			3			7	2				1				.	
•					PROERTY OF REPRODUCED	CELESTRA, IS ), USED OR			CELESTRA CAT.NO	CODE	IRE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D +0.015	G ±0.02	H ±0.01	·
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.					WP061434A		#6 Weld 61/24 =							
									137	#6 AWG	24.6 kcmil	1/4	1.56	0.44	0.09	0.75	0.26	
_																		_
D	l N	IOTE:	1 ΔΙΙ	DIMENSION	IS ADE IN IN	ICHES UNLESS	: OTHERWISE											D
		OTL.		CIFIED.	IO AILE III III	IONES ONLESC	OTTILITYIOL											
		<ol> <li>ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.</li> </ol>							B									
												—						
		OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.																
		WITH "P".																
	М	IATERIAL:	HIG	H CONDUCT	ΓΙVITY WRO	UGHT COPPER												
С	C FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.						E		Beveled wire entry									С
						FOR SILVER.		2 ( 11 ) ( 2										
										Wire inspection hole								
$\rightarrow$		INSTALLATION GUIDE								BOLT SIZE								
	DIE CODE = 24 DIE COLOR = Blue																	7
															Die C	color		
В	l⇔—G—≈l										В							
D									Color coded barrel markings—									
		C PLUS ROHS																
		WIF ZM	.ISTED RE CONNECTORS VV/2/7/8.E513813															
	1																	
											/ AR C	ELES	TRA	CO	RPO	RATIO	NC	
										76. Huancun Rd. Zhongcun Town.								
										www.huyaco.com		Panyu Dist. Guangzhou 511495.						
Α										TITLE WIRE CONNECTORS AND SOLDERING								Α
									_	LUGS FOR CODE AND FLEX CABLE								
	00	28-Oct-25	Ruby Feng	/ Feng Sinia Qiu Celestra Standards Spec. Initialed.				d.	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THE WROUGHT COPPER WP061434A-137 NTS							RID ANGLE PI	OJECTION	
	REV		DWN	CHK		DESCRI			ECN FII	VISH ELECTRO TII	DWG NO	186-cp43		NIIT	ICH .	<b>(</b>	$\exists$	
		l	4		I		3	/		2				111	1			'
			-		ı		-	_	Γ	_			I					