			4		1		3	7	7		2				1			
ı			ON THIS DRA			OF CELESTRA, IS ED, USED OR		,	CELESTRA CAT.NO	W	IRE SIZE	BOLT SIZE	B MIN	C ±0.04	D	G ±0.02	H ±0.01	
	DISLOSE	ED EXCEPT	FOR WHICH	FURNISHED.					LB061401AP	CODE - #6 AWG	#6 Weld 61/24 =		1.62	0.48	0.08	1.00	0.27	
									250		24.6 kcmil							
D	NO	DTE:		DIMENSION CIFIED.	NS ARE IN	INCHES UNLES	S OTHERWISE		_									D
			LIST	ED BY "UN	DERWRITE	) J SERIES OF C ERS INC." AND "( EX/24 STRANDE	CSA" FOR USE		B									
			OTH			' HAS NOT PEEF N THE SUFFIX C			98 × 5									
	МА	TERIAL:	HIGH	H CONDUC	TIVITY WR	OUGHT COPPE	₹											
С	FIN	IISH:	SPE	CIFED PLA	TE PER MI	LESS OTHERWIS L - T -16366. " FOR SILVER.	SE.		Beveled wire entry————————————————————————————————————									С
									—Wire inspection hole									
$\rightarrow$		STALLATIO						BOLT SIZE									$\leftarrow$	
		E COLOR =									C C				Die C	olor		
В	CUL)US ROHS								Color coded barrel markings									
			LIST WIRE CONN ZMVV/2/7/8															
		_																
										шп		ELES						
									HUYA® 76. Huancun Rd. Zhongcur www.huyaco.com Panyu Dist. Guangzhou 51							١.		
Α	$\vdash$									WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								
	$\vdash$		Ruby Feng				ards Spec. Initialed.			ATERIAL HIGH-COND WROUGHT (	COPPER LB061	101AP-25	0		TS	RID ANGLE PI	ROJECTION	
ı	REV	DATE	DWN	CHK		DESCR			N LCIV	ELECTRO TIN	N PLATE DWG. NO.	186-cp43	23   "	INIT IN	ICH -	<b>⊕</b> Ł		
			4				3	_		2					1			