DISCLOSED IN CONTIDENCY AND BOTTO BE REPRODUCED. USED OR DISCOSED EXCEPT FOR WHICH FURNISHED. NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX" AST AND "CSA" FOR USE ON CODE WIRES AND FLEX" AST AND "CSA" FOR USE ON CODE WIRES AND FLEX" AST AND FLEX FOR USE ON CODE WIRES AND FLEX" AST AND FLEX FOR USE ON CODE WIRES AND FLEX SEZE & 4/0 AWG S50/24 = 222		_	1		_		+	_			_		
DISCLOSED IN COMPIDENCE AND NOT TO BE REPRODUCED, USED OR DISLOSED EXCEPT FOR WHICH FURNISHED. DISLOSED EXCEPT FOR WHICH FURNISHED. 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DAIDBLALB WP AND J SERIES OF CAT NO. S ARE LISTED BY "UNDERWRITERS INC: AND "CSA" FOR USE ON CODE WIRES AND FLEXZ4 STRANDED CABLES. PRE-RIX CAT NO. WITH 1". HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL. T. 16366. SUFFIX CAT NO. WITH "SP" FOR SILVER. INSTALLATION GUIDE DIE CODE = 54 DIE CODE = 54 DIE COLOR = Purple NEBS 3 ROSS RESSON RESSON REBS 3 ROSS RESSON RESSO	1	1		POL-		_	V CELECTRA	3	TY OF CELESTRA IS	WING IS THE DROI	ON THIS DRA	E INIEODMATION	
DA4058-251 4/0 AWG 560/24 = 222 kcmil 4/0 Weld 5/8 2.68 1.33 1 DA4058-251 4/0 AWG 560/24 = 222 kcmil 4/0 Weld 5/8 2.68 1.33 1 Color coded marking PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFIED PLATE PER MIL. T. 16396. SUFFIX CAT.NO.WITH "SP" FOR SILVER. INSTALLATION GUIDE DIE CODE = 54 DIE CODE = 54 DIE CODE = 54 DIE COLOR = Purple B LISTED BY LINES OF CAT.NO. WITH "SP" FOR SILVER. DA4058-251 4/0 AWG 560/24 = 222 kcmil 4/0 Weld 5/8 2.68 1.33 1 COlor coded marking Bolt Size COLOR CODE MARKING BOLT SIZE A INSPECTION HOLE R Inspection Hole B Beveled entry	C 0.04 R ID ±0.01				-	-				NOT TO BE REPR	IFIDENCE AND	SCLOSED IN CON	
D NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DADBLALB, WP AND J. SERIES OF CAT.NO. S ARE LISTED BY 'UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR. THE PLATE UNLESS OTHERWISE SPECIFIED PLATE PER MIL. * T. 16396. SUFFIX CAT.NO.WITH "SP' FOR SILVER. INSTALLATION GUIDE DIE CODE = 54 D	1.19 1.35 0.65	1.33 1.19	5/8 2.68	1 5/X	1	4/0 AWG	DA4058-251			OTTAINOTIED.	101111111111111111111111111111111111111	PLOGED EXCELL	
NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DADBLALB, WP AND J SERIES OF CATINO. S ARE LISTED BY 'UNDERWRITERS INC.' AND 'CSA' FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CATINO WITH 'L' HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CATINO. WITH 'P'. MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL. T-16366. SUFFIX CATINO.WITH "SP" FOR SILVER. B INSTALLATION GUIDE DIE CODE = 64 DIE COLOR = Purple B R Inspection Hole B Beveiled entry				1/0 VVOIG	1 Komin	_ll							
SPECIFIED. 2. ALL DADBLAI, BWP AND J SERIES OF CATINO. S ARE LISTED BY 'UNDERWRITERS INC.' AND 'CSA' FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CATINO.WITH 'L' HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CATINO. WITH 'PSP' FOR SILVER. MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL. '1-16386. SUFFIX CATINO.WITH 'SP' FOR SILVER. B INSTALLATION GUIDE DIE CODE = 54 DIE COLOR = Purple NEBS3 NEBS3 NEBS3 NEBS3 Beveled entry	D		rkina	coded marki	olor co	Co							D
2. ALL DA.DB.LALB.WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T. 16366. SUFFIX CAT.NO.WITH "SP' FOR SILVER. INSTALLATION GUIDE DIE CODE = 64 DIE COLOR = Purple B WELCOMMOTION NEBS3 NEBS3 NEBS3 NEBS3 Beveled entry					JIOI GC	<u> </u>						NOTE:	
LISTED BY 'UNDERWRITERS INC.' AND 'CSA' FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT. NO. WITH 'L' HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH 'P'. MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFIED PLATE PER MIL. 1 - 16366. SUFFIX CAT.NO.WITH 'SP' FOR SILVER. INSTALLATION GUIDE DIE CODE = 54 DIE COLOR = Purple NEBS3 NEBS3 NEBS3 Beveled entry			Bolt Size	Bo				LNO.S ARE	AND J SERIES OF CA				
PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL T - 16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. INSTALLATION GUIDE DIE CODE = 54 DIE COLOR = Purple R Inspection Hole B EVELed entry			7 -			/	×-	SA" FOR USE	DERWRITERS INC." AND "CSA" FOR USE				
MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH 'SP' FOR SILVER. INSTALLATION GUIDE DIE CODE = 54 DIE COLOR = Purple R Inspection Hole B B B B B B B B B B B B B B B B B B	-			<		ODE							-
MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH 'SP' FOR SILVER. INSTALLATION GUIDE DIE CODE = 54 DIE COLOR = Purple R Inspection Hole B B B B B B B B B B B B B B B B B B					1 €								
C FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL. T. 16386. SUFFIX CAT.NO.WITH "SP" FOR SILVER. INSTALLATION GUIDE DIE CODE = 54 DIE COLOR = Purple R Inspection Hole B EVELECTOR R Inspection Hole B Beveled entry										∃ "P".	WITH		
SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. INSTALLATION GUIDE DIE CODE = 54 DIE COLOR = Purple R Inspection Hole B STALLATION GUIDE DIE COLOR = Number of the service of t				В	_							MATERIAL:	
INSTALLATION GUIDE DIE CODE = 54 DIE COLOR = Purple R Inspection Hole B NEBS3 EMS CE Beveled entry	С			-	A	Α							
B DIE CODE = 54 DIE COLOR = Purple NEBS3 ROHS CE Beveled entry Beveled entry			-	-		-	, -		"SP" FOR SILVER.	FIX CAT.NO.WIT	SUF		
B DIE CODE = 54 DIE COLOR = Purple NEBS3 ROHS CE Beveled entry Beveled entry													
B DIE CODE = 54 DIE COLOR = Purple NEBS3 ROHS CE Beveled entry Beveled entry													
B NEBS3 EN CE Beveled entry Beveled entry			n Hole	Inspection Ho	-i /	R	Ĩ-				54	DIE CODE =	
B REBS3 RES CE Beveled entry Beveled entry							- F				= Purple	DIE COLOR :	
NEBS3 CE Beveled entry Beveled entry						H	ੂੰ ∤						
NEBS3 CE Beveled entry Beveled entry]				<u> </u>						
LISTED WIRE CONNECTOR	В	i i		tn.	d optry	Povolod		CC	ne3 Rous	A NE			B
WIRE CONNECTOR				шу	u entry	Develed			D 2	NE	JUS 4	CAL	
											I IECTOR	LISTE WIRE CONN	
A 051 5070 4 0000	_												
A OFFECTRA CORR			_										
HUYA® CELESTRA CORP				® CELE	7 A (6	LIIV							
76. Huancun Rd. Zhon www.huyaco.com Panyu Dist. Guangzho													
				,									$_{A} \! \! \perp$
WIRE CONNECTORS AND SOLD LUGS FOR CODE AND FLEX CAL	JERING					I WIKE C							
MATERIAL USA SOLUTION AND A COALS	THRID ANGLE PROJECTION												
00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed. WROUGHT COPPER DA4058-251 NTS		NTS H	3-251	DA4058-251	OPPER	WROUGHT COI		<u>'</u>					_
REVIDATE DVVIN CHR DESCRIPTION ELECTROTIN PLATE 186-cp0434 INCH		"" INCH	6-cp0434	186-cp(PLATE	ELECTRO TIN PI	ECN		DESCRIF	CHK		V DATE	
4 3 2	1	1				2	4	3			4		